



Windows PowerShell Get-Help on Cmdlet 'Add-AzDataLakeStoreItemContent'

PS:\>Get-HELP Add-AzDataLakeStoreItemContent -Full

NAME

Add-AzDataLakeStoreItemContent

SYNOPSIS

Adds content to an item in a Data Lake Store.

SYNTAX

```
Add-AzDataLakeStoreItemContent [-Account] <System.String> [-Path]
<Microsoft.Azure.Commands.DataLakeStore.Models.DataLakeStorePathInstance> [-Value] <System.Object>
[[[-Encoding] <System.Text.Encoding>] [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
[<CommonParameters>]
```

DESCRIPTION

The Add-AzDataLakeStoreItemContent cmdlet adds content to an item in an Azure Data Lake Store.

-Account <System.String>

Specifies the name of the Data Lake Store account.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Encoding <System.Text.Encoding>

Specifies the encoding for the item to create. The acceptable values for this parameter are: - Unknown

- String

- Unicode

- Byte

- BigEndianUnicode

- UTF8

- UTF7

- Ascii

- Default

- Oem

- BigEndianUTF32

Required? false

Position? 3

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Path <Microsoft.Azure.Commands.DataLakeStore.Models.DataLakeStorePathInstance>

Specifies the Data Lake Store path of the item to modify, starting with the root directory (/).

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Value <System.Object>

Specifies the content to add to the item.

Required? true

Position? 2

Default value None

Accept pipeline input? True (ByPropertyName, ByValue)

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

System.String

Microsoft.Azure.Commands.DataLakeStore.Models.DataLakeStorePathInstance

System.Object

System.Text.Encoding

OUTPUTS

System.Boolean

NOTES

----- Example 1: Add content to a file -----

Add-AzDataLakeStoreItemContent -AccountName "ContosoADLS" -Path /abc/myFile.txt -Value "My content here"

This command adds content to the file myFile.txt.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.datalakestore/add-azdatalakestoreitemcontent>

Get-AzDataLakeStoreItemContent