



Windows PowerShell Get-Help on Cmdlet 'Clear-AzSqlDatabaseVulnerabilityAssessmentSetting'

PS:\>Get-HELP Clear-AzSqlDatabaseVulnerabilityAssessmentSetting -Full

NAME

Clear-AzSqlDatabaseVulnerabilityAssessmentSetting

SYNOPSIS

Clears the vulnerability assessment settings of a database.

SYNTAX

```
Clear-AzSqlDatabaseVulnerabilityAssessmentSetting [-ResourceGroupName] <System.String> [-ServerName]
<System.String> [-DatabaseName] <System.String> [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-InputObject
<Microsoft.Azure.Commands.Sql.Database.Model.AzureSqlDatabaseModel>] [-Confirm] [-WhatIf]
[<CommonParameters>]
```

DESCRIPTION

The Clear-AzSqlDatabaseVulnerabilityAssessmentSetting cmdlet removes the vulnerability assessment settings of an Azure SQL Database. Note that you need to run

Enable-AzSqlServerAdvancedDataSecurity cmdlet as a prerequisite for using this cmdlet.

PARAMETERS

-DatabaseName <System.String>

SQL Database name.

Required? true

Position? 2

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-InputObject <Microsoft.Azure.Commands.Sql.Database.Model.AzureSqlDatabaseModel>

The database object to clear Vulnerability Assessment settings for

Required? false

Position? named

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-ResourceGroupName <System.String>

The name of the resource group.

Required? true

Position? 0
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-ServerName <System.String>

SQL Database server name.

Required? true
Position? 1
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

System.String

Microsoft.Azure.Commands.Sql.Database.Model.AzureSqlDatabaseModel

OUTPUTS

Microsoft.Azure.Commands.Sql.VulnerabilityAssessment.Model.DatabaseVulnerabilityAssessmentSettingsModel

NOTES

Example 1: Clear the vulnerability assessment settings of an Azure SQL database

Clear-AzSqlDatabaseVulnerabilityAssessmentSetting `

-ResourceGroupName "ResourceGroup01" `

-ServerName "Server01" `

-DatabaseName "Database01"

Example 2: Clear the vulnerability assessment settings from a database object

```
Get-AzSqlDatabase `
    -ResourceGroupName "ResourceGroup01" `
    -ServerName "Server01" `
    -DatabaseName "Database01" `
| Clear-AzSqlDatabaseVulnerabilityAssessmentSetting
```

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.sql/clear-azsqldatabasevulnerabilityassessmentsetting>