MyWebUniversity*







Full credit is given to the above companies including the OS that this TDF file was generated!

PowerShell Get-Help on command 'Clear-Recyclebin'

PS C:\Users\wahid> Get-Help Clear-Recyclebin

NAME

Clear-RecycleBin

SYNOPSIS

Clears the contents of the current user's recycle bin.

SYNTAX

Clear-RecycleBin [[-DriveLetter] <System.String[]>] [-Force] [-Confirm] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The `Clear-RecycleBin` cmdlet deletes the content of the current user's recycle bin. This action is like using Windows Empty Recycle Bin .

PARAMETERS

-DriveLetter <System.String[]>
Specifies the recycle bin to clear for a single drive letter or an array of drive letters.

-Force <system.management.automation.switchparameter></system.management.automation.switchparameter>
Specifies that the user isn't prompted for confirmation to clear a recycle
bin. The Force parameter also overrides the WhatIf and Confirm parameters.
-Confirm <system.management.automation.switchparameter></system.management.automation.switchparameter>
Prompts for user confirmation before running the cmdlet. The user is
prompted for confirmation even if the Confirm parameter isn't specified.
-WhatIf <system.management.automation.switchparameter></system.management.automation.switchparameter>
Shows what would happen if `Clear-RecycleBin` runs. The cmdlet isn't run.
<commonparameters></commonparameters>
This cmdlet supports the common parameters: Verbose, Debug,
ErrorAction, ErrorVariable, WarningAction, WarningVariable,
OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (https:/go.microsoft.com/fwlink/?LinkID=113216)
1: Clear all recycle bins
Clear-RecycleBin
Confirm
Are you sure you want to perform this action?
Performing the operation "Clear-RecycleBin" on target "All of the contents of
the Recycle Bin".
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default
is "Y"):

`Clear-RecycleBin` prompts the user for confirmation.

----- 2: Clear a specified recycle bin ------

`Clear-RecycleBin` uses the DriveLetter parameter to specify the recycle bin on the `C` volume. The user is prompted for confirmation to run the command. ------ 3: Clear all recycle bins without confirmation ------

Clear-RecycleBin -Force

`Clear-RecycleBin` uses the Force parameter and doesn't prompt the user for confirmation to clear all recycle bins.

An alternative is to replace `-Force` with `-Confirm:\$false`.

REMARKS

To see the examples, type: "get-help Clear-RecycleBin -examples".

For more information, type: "get-help Clear-RecycleBin -detailed".

For technical information, type: "get-help Clear-RecycleBin -full".

For online help, type: "get-help Clear-RecycleBin -online"