



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Disable-AppvClientConnectionGroup'

PS C:\Users\wahid> Get-Help Disable-AppvClientConnectionGroup

NAME

Disable-AppvClientConnectionGroup

SYNOPSIS

Disables a connection group on the computer running the App-V client.

SYNTAX

Disable-AppvClientConnectionGroup [-ConnectionGroup]

<AppvClientConnectionGroup> [-Global] [-UserSID <String>] [<CommonParameters>]

Disable-AppvClientConnectionGroup [-GroupId] <Guid> [-VersionId] <Guid>

[-Global] [-UserSID <String>] [<CommonParameters>]

Disable-AppvClientConnectionGroup [-Name] <String> [-Global] [-UserSID

<String>] [<CommonParameters>]

DESCRIPTION

The Disable-AppvClientConnectionGroup cmdlet disables an already existing connection group on the computer that runs the Microsoft Application

Virtualization (App-V) client.

PARAMETERS

-ConnectionGroup <AppvClientConnectionGroup>

Specifies an App-V Connection Group object.

-Global [<SwitchParameter>]

Indicates that this cmdlet disables the connection group is disabled for all users that log into the target computer. Otherwise, it disables the connection group only for the currently running user.

-GroupId <Guid>

Specifies the GUID associated with a specific connection group.

-Name <String>

Specifies the name of the App-V connection group.

-UserSID <String>

Specifies the SID of the intended user, in the form of S-1-2-34-56789012-3456789012-345678901-2345. This parameter requires elevated rights to run.

-VersionId <Guid>

Specifies a GUID that differentiates the connection group version from other versions. If you do not specify this parameter, the cmdlet operates on all versions of the connection group.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

--- Example 1: Disable a connection group by using its name ---

```
PS C:\> Disable-AppvClientConnectionGroup -Name "MyGroup"
```

This command disables the connection group named MyGroup.

---- Example 2: Disable a connection group by using its ID ----

```
PS C:\> Disable-AppvClientConnectionGroup -GroupID  
35ec9e5f-ab21-463f-8fe6-b90d4b66d182
```

This command disables the connection group that has the group ID
35ec9e5f-ab21-463f-8fe6-b90d4b66d182.

Example 3: Disable all connection groups by names that match a string

```
PS C:\> Get-AppvClientConnectionGroup -Name "MyGr*" |  
Disable-AppvClientConnectionGroup
```

This command gets all the connection groups that have the string MyGr in the
name, and then disables them.

REMARKS

To see the examples, type: "get-help Disable-AppvClientConnectionGroup
-examples".

For more information, type: "get-help Disable-AppvClientConnectionGroup
-detailed".

For technical information, type: "get-help Disable-AppvClientConnectionGroup
-full".

For online help, type: "get-help Disable-AppvClientConnectionGroup -online"