



Windows PowerShell Get-Help on Cmdlet 'Disable-AzFrontDoorCustomDomainHttps'

PS:\>Get-HELP Disable-AzFrontDoorCustomDomainHttps -Full

NAME

Disable-AzFrontDoorCustomDomainHttps

SYNOPSIS

Disable HTTPS for a custom domain

SYNTAX

Disable-AzFrontDoorCustomDomainHttps [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -FrontDoorName

<System.String> -FrontendEndpointName <System.String> -ResourceGroupName <System.String> [-Confirm] [-WhatIf]

[<CommonParameters>]

Disable-AzFrontDoorCustomDomainHttps [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -InputObject

<Microsoft.Azure.Commands.FrontDoor.Models.PSFrontendEndpoint> [-Confirm] [-WhatIf] [<CommonParameters>]

Disable-AzFrontDoorCustomDomainHttps [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -ResourceId

<System.String> [-Confirm] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The Disable-AzFrontDoorCustomDomainHttps disables HTTPS for a custom domain.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-FrontDoorName <System.String>

The name of the Front Door.

Required? true

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-FrontendEndpointName <System.String>

Frontend endpoint name.

Required? true

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-InputObject <Microsoft.Azure.Commands.FrontDoor.Models.PSFrontendEndpoint>

The Frontend endpoint object to update.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-ResourceGroupName <System.String>

The resource group to which the Front Door belongs.

Required? true

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-ResourceId <System.String>

Resource Id of the Front Door endpoint to disable https

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,
ErrorAction, ErrorVariable, WarningAction, WarningVariable,
OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

System.String

OUTPUTS

Microsoft.Azure.Commands.FrontDoor.Models.PSFrontendEndpoint

NOTES

Example 1: Disable HTTPS for a custom domain with FrontDoorName and ResourceGroupName.

```
Disable-AzFrontDoorCustomDomainHttps -ResourceGroupName "resourcegroup1" -FrontDoorName "frontdoor1"
-FrontendEndpointName "frontendpointname1-custom-xyz"
```

```
HostName                : frontendpointname1.custom.xyz
SessionAffinityEnabledState : Disabled
SessionAffinityTtlSeconds : 0
WebApplicationFirewallPolicyLink :
Backends                :
CustomHttpsProvisioningState : Disabling
CustomHttpsProvisioningSubstate : DeletingCertificate
CertificateSource        : FrontDoor
ProtocolType             : ServerNameIndication
Vault                    :
SecretName                :
SecretVersion             :
CertificateType           :
ResourceState             : Enabled
Id                        : /subscriptions/{guid}/resourcegroups/resourcegroup1
```

```
/providers/Microsoft.Network/frontdoors/frontdoor1/frontendendpoints/frontendpointname1-custom-xyz
```

```
Name                : frontendpointname1-custom-xyz
Type                : Microsoft.Network/frontdoors/frontendendpoints
```

Disable HTTPS for a custom domain "frontendpointname1-custom-xyz" with FrontDoorName as "frontdoor1" and ResourceGroupName as "resourcegroup1".

Example 2: Disable HTTPS for a custom domain with PSFrontendEndpoint object.

```
Get-AzFrontDoorFrontendEndpoint -ResourceGroupName "resourcegroup1" -FrontDoorName "frontdoor1" -Name
```

"frontendpointname1-custom-xyz" |

Disable-AzFrontDoorCustomDomainHttps -InputObject \$frontendEndpointObj

HostName : frontendpointname1.custom.xyz

SessionAffinityEnabledState : Disabled

SessionAffinityTtlSeconds : 0

WebApplicationFirewallPolicyLink :

Backends :

CustomHttpsProvisioningState : Disabling

CustomHttpsProvisioningSubstate : DeletingCertificate

CertificateSource : FrontDoor

ProtocolType : ServerNameIndication

Vault :

SecretName :

SecretVersion :

CertificateType :

ResourceState : Enabled

Id : /subscriptions/{guid}/resourcegroups/resourcegroup1

/providers/Microsoft.Network/frontdoors/frontdoor1/frontendendpoints/frontendpointname1-custom-xyz

Name : frontendpointname1-custom-xyz

Type : Microsoft.Network/frontdoors/frontendendpoints

Disable HTTPS for a custom domain with PSFrontendEndpoint object.

Example 3: Disable HTTPS for a custom domain with ResourceId.

Disable-AzFrontDoorCustomDomainHttps -ResourceId \$resourceId

HostName : frontendpointname1.custom.xyz

SessionAffinityEnabledState : Disabled

SessionAffinityTtlSeconds : 0

WebApplicationFirewallPolicyLink :

Backends :

CustomHttpsProvisioningState : Disabling

CustomHttpsProvisioningSubstate : DeletingCertificate

CertificateSource : FrontDoor

ProtocolType : ServerNameIndication

Vault :

SecretName :

SecretVersion :

CertificateType :

ResourceState : Enabled

Id : /subscriptions/{guid}/resourcegroups/resourcegroup1

/providers/Microsoft.Network/frontdoors/frontdoor1/frontendendpoints/frontendpointname1-custom-xyz

Name : frontendpointname1-custom-xyz

Type : Microsoft.Network/frontdoors/frontendendpoints

Disable HTTPS for a custom domain "frontendpointname1-custom-xyz" with ResourceId as \$resourceId.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.frontdoor/disable-azfrontdoorcustomdomainhttps>