



Windows PowerShell Get-Help on Cmdlet 'Disable-AzOperationalInsightsLinuxCustomLogCollection'

PS:\>Get-HELP Disable-AzOperationalInsightsLinuxCustomLogCollection -Full

NAME

Disable-AzOperationalInsightsLinuxCustomLogCollection

SYNOPSIS

Stops collection of custom logs from Linux computers.

SYNTAX

```
Disable-AzOperationalInsightsLinuxCustomLogCollection [-ResourceGroupName] <System.String> [-WorkspaceName]
<System.String> [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Confirm] [-WhatIf]
[<CommonParameters>]
```

```
Disable-AzOperationalInsightsLinuxCustomLogCollection [-Workspace]
<Microsoft.Azure.Commands.OperationalInsights.Models.PSWorkspace> [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Confirm] [-WhatIf]
[<CommonParameters>]
```

DESCRIPTION

The `Disable-AzOperationalInsightsLinuxCustomLogCollection` cmdlet stops collection of custom logs from connected Linux computers in a workspace.

PARAMETERS

`-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>`

The credentials, account, tenant, and subscription used for communication with azure

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

`-ResourceGroupName <System.String>`

Specifies the name of a resource group that contains Linux computers.

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

`-Workspace <Microsoft.Azure.Commands.OperationalInsights.Models.PSWorkspace>`

Specifies a workspace in which this cmdlet operates.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

`-WorkspaceName <System.String>`

Specifies the name of a workspace in which this cmdlet operates.

Required?	true
Position?	2
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

System.String

OUTPUTS

Microsoft.Azure.Commands.OperationalInsights.Models.PSDataSource

NOTES

* Keywords: azure, azurearm, arm, resource, management, manager, operational, insights

----- Example 1 -----

Disable-AzOperationalInsightsLinuxCustomLogCollection -ResourceGroupName test-rg -WorkspaceName

OperationalInsight

Name : DataSource_CustomLogCollection

ResourceGroupName : test-rg

WorkspaceName : OperationalInsight

ResourceId

:

/subscriptions/xxxx-xxxx-xxxx-xxxx-xxxx/resourceGroups/test-rg/providers/Microsoft.OperationalInsights/wo

rkspaces/OperationalInsight/datasources/DataSource_CustomLogCollection

Kind : CustomLogCollection

Properties : {"state":"LinuxLogsDisabled"}

Stops collection of custom logs from connected Linux computers in a workspace.

RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.operationalinsights/disable-azoperationalinsightslinuxcustomlogcollection>

Enable-AzOperationalInsightsLinuxCustomLogCollection