



Windows PowerShell Get-Help on Cmdlet 'Disable-AzRecoveryServicesBackupRPMountScript'

PS:\>Get-HELP Disable-AzRecoveryServicesBackupRPMountScript -Full

NAME

Disable-AzRecoveryServicesBackupRPMountScript

SYNOPSIS

Dismounts all the files of the recovery point.

SYNTAX

Disable-AzRecoveryServicesBackupRPMountScript [-RecoveryPoint]

<Microsoft.Azure.Commands.RecoveryServices.Backup.Cmdlets.Models.RecoveryPointBase> [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-PassThru] [-VaultId

<System.String>] [-Confirm] [-WhatIf]

[<CommonParameters>]

DESCRIPTION

The Disable-AzRecoveryServicesBackupRPMountScript cmdlet dismounts the files of the recovery point which were mounted earlier using the

Get-AzRecoveryServicesBackupRPMountScript cmdlet.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-PassThru <System.Management.Automation.SwitchParameter>

Return the recovery point.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-RecoveryPoint <Microsoft.Azure.Commands.RecoveryServices.Backup.Cmdlets.Models.RecoveryPointBase>

Recovery point object to be restored

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-VaultId <System.String>

ARM ID of the Recovery Services Vault.

Required? false

Position? named
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.Commands.RecoveryServices.Backup.Cmdlets.Models.RecoveryPointBase

System.String

OUTPUTS

Microsoft.Azure.Commands.RecoveryServices.Backup.Cmdlets.Models.RecoveryPointBase

NOTES

----- Example 1: Dismount a recovery point -----

```
$namedContainer = Get-AzRecoveryServicesBackupContainer -ContainerType "AzureVM" -Status "Registered"
-FriendlyName "V2VM"

$backupitem = Get-AzRecoveryServicesBackupItem -Container $namedContainer -WorkloadType "AzureVM"

$startDate = (Get-Date).AddDays(-7)

$endDate = Get-Date

$rp = Get-AzRecoveryServicesBackupRecoveryPoint -Item $backupitem -StartDate $startdate.ToUniversalTime()
-EndDate $enddate.ToUniversalTime()
```

<# To mount files of the latest recovery point, obtain the script by #>

```
Get-AzRecoveryServicesBackupRPMountScript -RecoveryPoint $rp[0]
```

```
OsType Password      Filename
```

```
-----
```

Windows

e3632984e51f496

V2VM_wus2_8287309959960546283_451516692429_cbd6061f7fc543c489f1974d33659fed07a6e0c2e08740.exe

<# When the script is run, it will mount the files of the recovery point \$rp[0]

After the relevant files are copied, then you remove the files of the recovery point by running the disable cmdlet #>

Disable-AzRecoveryServicesBackupRPMountScript -RecoveryPoint \$rp[0]

----- Example 2 -----

Disable-AzRecoveryServicesBackupRPMountScript -Confirm -RecoveryPoint \$rp[0] -VaultId \$vault.ID

RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.recoveryservices/disable-azrecoveryservicesbackuprpmountscript>