



**Full credit is given to all the above companies including the Operating System that this PDF file was generated!**

### ***Windows PowerShell Get-Help on Cmdlet 'Disable-AzureRmAlias'***

**PS:\>Get-HELP Disable-AzureRmAlias -Full**

#### **NAME**

Disable-AzureRmAlias

#### **SYNOPSIS**

Disables AzureRm prefix aliases for Az modules.

#### **SYNTAX**

Disable-AzureRmAlias  <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>  <System.String[]>  [-PassThru] [-Scope {Process   CurrentUser   LocalMachine}] [-Confirm] [-WhatIf] [<CommonParameters>]	[ -DefaultProfile ]  [-Module ]  [-Module ]
---	---

#### **DESCRIPTION**

Disables AzureRm prefix aliases for Az modules. If -Module is specified, only modules listed will have aliases disabled. Otherwise all AzureRm aliases are disabled.

#### **PARAMETERS**

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Module <System.String[]>

Indicates which modules to disable aliases for. If none are specified, default is all enabled modules.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-PassThru <System.Management.Automation.SwitchParameter>

If specified, cmdlet will return all disabled aliases

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-Scope <System.String>

Indicates what scope aliases should be disabled for. Default is 'Process'

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,

OutBuffer, PipelineVariable, and OutVariable. For more information, see

about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

## INPUTS

None

## OUTPUTS

System.String

## NOTES

----- Example 1 -----

Disable-AzureRmAlias

Disables all AzureRm prefixes for the current PowerShell session.

----- Example 2 -----

Disable-AzureRmAlias -Module Az.Accounts -Scope CurrentUser

Disables AzureRm aliases for the Az.Accounts module for both the current process and for the current user.

## RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.accounts/disable-azurermalias>