



Windows PowerShell Get-Help on Cmdlet 'Disable-NetAdapterRss'

PS:\>Get-HELP Disable-NetAdapterRss -Full

NAME

Disable-NetAdapterRss

SYNOPSIS

Disables RSS on a network adapter.

SYNTAX

```
Disable-NetAdapterRss [-Name] <String[]> [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-IncludeHidden]
[-NoRestart] [-PassThru] [-ThrottleLimit <Int32>] [-WhatIf]
[<CommonParameters>]
```

```
Disable-NetAdapterRss [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-IncludeHidden] -InterfaceDescription
<String[]> [-NoRestart] [-PassThru] [-ThrottleLimit
<Int32>] [-WhatIf] [<CommonParameters>]
```

```
Disable-NetAdapterRss [-AsJob] [-CimSession <CimSession[]>] [-Confirm] -InputObject <CimInstance[]> [-NoRestart]
[-PassThru] [-ThrottleLimit <Int32>] [-WhatIf]
[<CommonParameters>]
```

DESCRIPTION

The Disable-NetAdapterRss cmdlet disables receive side scaling (RSS) on a network adapter. RSS is a scalability technology that distributes the receive network

traffic among multiple processors by hashing the header of the incoming packet. Without RSS in firstref_longhorn and later, network traffic is processed on the first

processor which can quickly reach full utilization limiting receive network throughput. Running this cmdlet can reduce the performance of servers running Windows

Server 2012 and later. Various properties can be configured to optimize the performance of RSS.

PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete. The cmdlet immediately returns an object that

represents the job and then displays the command prompt. You can continue to work in the session while the job completes. To manage the job, use the `*-Job`

cmdlets. To get the job results, use the Receive-Job (<https://go.microsoft.com/fwlink/?LinkID=113372>)cmdlet. For more information about Windows PowerShell

background jobs, see about_Jobs (<https://go.microsoft.com/fwlink/?LinkID=113251>).

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a New-CimSession

(<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or

[Get-CimSession](<https://go.microsoft.com/fwlink/p/?LinkId=227966>)cmdlet. The default is the current session

on the local computer.

| | |
|-----------------------------|-------|
| Required? | false |
| Position? | named |
| Default value | None |
| Accept pipeline input? | False |
| Accept wildcard characters? | false |

-Confirm [<SwitchParameter>]

Prompts you for confirmation before running the cmdlet.

| | |
|-----------------------------|-------|
| Required? | false |
| Position? | named |
| Default value | False |
| Accept pipeline input? | False |
| Accept wildcard characters? | false |

-IncludeHidden [<SwitchParameter>]

Indicates that the cmdlet includes both visible and hidden network adapters in the operation. By default only visible network adapters are included. If a wildcard character is used in identifying a network adapter and this parameter has been specified, then the wildcard string is matched against both hidden and visible network adapters.

| | |
|-----------------------------|-------|
| Required? | false |
| Position? | named |
| Default value | False |
| Accept pipeline input? | False |
| Accept wildcard characters? | false |

-InputObject <CimInstance[]>

Specifies the input to this cmdlet. You can use this parameter, or you can pipe the input to this cmdlet.

| | |
|-----------|------|
| Required? | true |
|-----------|------|

Position? named
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-InterfaceDescription <String[]>

Specifies an array of network adapter interface descriptions. For a physical network adapter this is typically the name of the vendor of the network adapter

followed by a part number and description, such as `"Contoso 12345 Gigabit Network Device"`.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Name <String[]>

Specifies an array of network adapter names.

Required? true
Position? 0
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-NoRestart [<SwitchParameter>]

Indicates that the cmdlet does not restart the network adapter after completing the operation. Many advanced properties require restarting the network adapter before the new settings take effect.

Required? false
Position? named
Default value False

Accept pipeline input? False

Accept wildcard characters? false

`-PassThru [<SwitchParameter>]`

Returns an object representing the item with which you are working. By default, this cmdlet does not generate any output.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

`-ThrottleLimit <Int32>`

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then

Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit

applies only to the current cmdlet, not to the session or to the computer.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

`-WhatIf [<SwitchParameter>]`

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Management.Infrastructure.CimInstance#ROOT/StandardCimv2/MSFT_NetAdapterRssSettingData[]

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the pound sign (`#`) provides the namespace and class name for the underlying WMI object.

OUTPUTS

Microsoft.Management.Infrastructure.CimInstance#ROOT/StandardCimv2/MSFT_NetAdapterRssSettingData

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the pound sign (`#`) provides the namespace and class name for the underlying WMI object.

NOTES

--- Example 1: Disable RSS on the specified network adapter ---

```
PS C:\> Disable-NetAdapterRss -Name "MyAdapter"
```

This command disables RSS on the network adapter named MyAdapter and restarts the network adapter.

RELATED LINKS

Online

Version:

https://learn.microsoft.com/powershell/module/netadapter/disable-netadapterrss?view=windowsserver2022-ps&wt.mc_id=ps-gethelp

Enable-NetAdapterRss

Get-NetAdapterRss

Set-NetAdapterRss