



Windows PowerShell Get-Help on Cmdlet 'Edit-AzDataProtectionPolicyTagClientObject'

PS:\>Get-HELP Edit-AzDataProtectionPolicyTagClientObject -Full

NAME

Edit-AzDataProtectionPolicyTagClientObject

SYNOPSIS

Adds or removes schedule tag in an existing backup policy.

SYNTAX

Edit-AzDataProtectionPolicyTagClientObject -Policy <IBackupPolicy> -Name {Daily | Weekly | Monthly | Yearly}
-RemoveRule [<CommonParameters>]

Edit-AzDataProtectionPolicyTagClientObject -Policy <IBackupPolicy> -Name {Daily | Weekly | Monthly | Yearly} -Criteria
<IScheduleBasedBackupCriteria[]>
[<CommonParameters>]

DESCRIPTION

Adds or removes schedule tag in an existing backup policy.

PARAMETERS

-Policy <IBackupPolicy>

Backup Policy Object.

To construct, see NOTES section for POLICY properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name

Name of the Schedule tag.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-RemoveRule [<SwitchParameter>]

Specify whether to remove the tag from the given policy object.

Required? true

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Criteria <IScheduleBasedBackupCriteria[]>

Criteria to be associated with the schedule tag.

To construct, see NOTES section for CRITERIA properties and create a hash table.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.DataProtection.Models.Api20240401.IBackupPolicy

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

CRITERIA <IScheduleBasedBackupCriteria[]>: Criterias to be associated with the schedule tag.

ObjectType <String>: Type of the specific object - used for deserializing

[AbsoluteCriterion <AbsoluteMarker[]>]: it contains absolute values like "AllBackup" / "FirstOfDay" / "FirstOfWeek" / "FirstOfMonth" and should be part of AbsoluteMarker enum

[DaysOfMonth <IDay[]>]: This is day of the month from 1 to 28 other wise last of month

[Date <Int32?>]: Date of the month

[IsLast <Boolean?>]: Whether Date is last date of month

[DaysOfTheWeek <DayOfWeek[]>]: It should be Sunday/Monday/T..../Saturday

[MonthsOfYear <Month[]>]: It should be January/February/...../December

[ScheduleTime <DateTime[]>]: List of schedule times for backup

[WeeksOfTheMonth <WeekNumber[]>]: It should be First/Second/Third/Fourth/Last

POLICY <IBackupPolicy>: Backup Policy Object.

DatasourceType <String[]>: Type of datasource for the backup management

ObjectType <String>:

PolicyRule <IBasePolicyRule[]>: Policy rule dictionary that contains rules for each backuptype i.e

Full/Incremental/Logs etc

Name <String>:

ObjectType <String>:

DataStoreObjectType <String>: Type of Datasource object, used to initialize the right inherited type

DataStoreType <DataStoreTypes>: type of datastore; Operational/Vault/Archive

TriggerObjectType <String>: Type of the specific object - used for deserializing

Lifecycle <ISourceLifeCycle[]>:

DeleteAfterDuration <String>: Duration of deletion after given timespan

DeleteAfterObjectType <String>: Type of the specific object - used for deserializing

SourceDataStoreObjectType <String>: Type of Datasource object, used to initialize the right inherited type

SourceDataStoreType <DataStoreTypes>: type of datastore; Operational/Vault/Archive

[TargetDataStoreCopySetting <ITargetCopySetting[]>]:

CopyAfterObjectType <String>: Type of the specific object - used for deserializing

DataStoreObjectType <String>: Type of Datasource object, used to initialize the right inherited type

DataStoreType <DataStoreTypes>: type of datastore; Operational/Vault/Archive

[BackupParameterObjectType <String>]: Type of the specific object - used for deserializing

[IsDefault <Boolean?>]:

----- EXAMPLE 1 -----

PS C:\>\$criteria = New-AzDataProtectionPolicyTagCriteriaClientObject -AbsoluteCriteria FirstOfWeek

Edit-AzDataProtectionPolicyTagClientObject -Policy \$pol -Name Weekly -Criteria \$criteria

----- EXAMPLE 2 -----

PS C:\>Edit-AzDataProtectionPolicyTagClientObject -Policy \$pol -Name Weekly -RemoveRule

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.dataprotection/edit-azdataprotectionpolicytagclientobject>