



Windows PowerShell Get-Help on Cmdlet 'Enable-AzAdvisorRecommendation'

PS:\>Get-HELP Enable-AzAdvisorRecommendation -Full

NAME

Enable-AzAdvisorRecommendation

SYNOPSIS

Enables Azure Advisor recommendation(s).

SYNTAX

```
Enable-AzAdvisorRecommendation -ResourceId <String> [-SubscriptionId <String[]>] [-DefaultProfile <PSObject>]
[-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
    [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Enable-AzAdvisorRecommendation [-SubscriptionId <String[]>] -RecommendationName <String> [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
    [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Enable-AzAdvisorRecommendation [-SubscriptionId <String[]>] -InputObject <IAdvisorIdentity> [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend
```

<SendAsyncStep[]> [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]

DESCRIPTION

Enables Azure Advisor recommendation(s).

PARAMETERS

-ResourceId <String>

Id of the recommendation to be suppressed.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String[]>

The Azure subscription ID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-RecommendationName <String>

ResourceName of the recommendation.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IAdvisorIdentity>

The powershell object type PsAzureAdvisorResourceRecommendationBase returned by Get-AzAdvisorRecommendation call.

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-DefaultProfile <PSObject>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Advisor.Models.IAdvisorIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Advisor.Models.Api202001.IResourceRecommendationBase

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IAdvisorIdentity>: The powershell object type PsAzureAdvisorResourceRecommendationBase returned by Get-AzAdvisorRecommendation call.

[ConfigurationName <ConfigurationName?>]: Advisor configuration name. Value must be 'default'

[Id <String>]: Resource identity path

[Name <String>]: Name of metadata entity.

[OperationId <String>]: The operation ID, which can be found from the Location field in the generate recommendation response header.

[RecommendationId <String>]: The recommendation ID.

[ResourceGroup <String>]: The name of the Azure resource group.

[ResourceUri <String>]: The fully qualified Azure Resource Manager identifier of the resource to which the recommendation applies.

[SubscriptionId <String>]: The Azure subscription ID.

----- EXAMPLE 1 -----

PS

C:\>Enable-AzAdvisorRecommendation

-ResourceId

/subscriptions/9e223dbe-3399-4e19-88eb-0975f02ac87f/resourcegroups/automanagehcrprg/providers/microsoft.compute/virtualmachines/arcbox-capi-mgmt/providers/Microsoft.Advisor/recommendations/42963553-61de-5334-2d2e-47f3a0099d41

----- EXAMPLE 2 -----

PS C:\>Enable-AzAdvisorRecommendation -RecommendationName 42963553-61de-5334-2d2e-47f3a0099d41

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.advisor/Enable-AzAdvisorRecommendation>