



Windows PowerShell Get-Help on Cmdlet 'Enable-AzSqlDatabaseSensitivityRecommendation'

PS:\>Get-HELP Enable-AzSqlDatabaseSensitivityRecommendation -Full

NAME

Enable-AzSqlDatabaseSensitivityRecommendation

SYNOPSIS

Enables sensitivity recommendations on columns (recommendations are enabled by default on all columns) in the database.

SYNTAX

```
Enable-AzSqlDatabaseSensitivityRecommendation [-ResourceGroupName] <System.String> [-ServerName]
<System.String> [-DatabaseName] <System.String> [-AsJob] -ColumnName
<System.String> [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-PassThru]
-SchemaName <System.String>
-TableName <System.String> [-Confirm] [-WhatIf] [<CommonParameters>]
```

```
Enable-AzSqlDatabaseSensitivityRecommendation [-AsJob] -ColumnName <System.String> -DatabaseObject
<Microsoft.Azure.Commands.Sql.Database.Model.AzureSqlDatabaseModel>
[-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
[-PassThru] -SchemaName <System.String> -TableName
```

<System.String> [-Confirm] [-WhatIf] [<CommonParameters>]

Enable-AzSqlDatabaseSensitivityRecommendation [-AsJob] [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]

-InputObject <Microsoft.Azure.Commands.Sql.DataClassification.Model.SqlDatabaseSensitivityClassificationModel>

[-PassThru] [-Confirm] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The Enable-AzSqlDatabaseSensitivityRecommendation cmdlet enables sensitivity recommendations on columns in the database.

PARAMETERS

-AsJob <System.Management.Automation.SwitchParameter>

Run cmdlet in the background

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-ColumnName <System.String>

Name of column.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DatabaseName <System.String>

The name of the Azure SQL database.

Required? true
Position? 2
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-DatabaseObject <Microsoft.Azure.Commands.Sql.Database.Model.AzureSqlDatabaseModel>

The SQL database object.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-InputObject <Microsoft.Azure.Commands.Sql.DataClassification.Model.SqlDatabaseSensitivityClassificationModel>

An object representing a SQL Database Sensitivity Classification.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-PassThru <System.Management.Automation.SwitchParameter>

Specifies whether to output the sensitivity classification model at end of cmdlet execution

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-ResourceGroupName <System.String>

The name of the resource group.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-SchemaName <System.String>

Name of schema.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ServerName <System.String>

SQL server name.

Required? true

Position? 1
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-TableName <System.String>

Name of table.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.Sql.DataClassification.Model.SqlDatabaseSensitivityClassificationModel

OUTPUTS

System.Boolean

NOTES

Example 1: Enable sensitivity recommendations on a given column in an Azure SQL Database.

```
Enable-AzSqlDatabaseSensitivityRecommendation -ResourceGroupName resourceGroup -ServerName server  
-DatabaseName database -SchemaName schema -TableName table  
-ColumnName column
```

Example 2: Enable sensitivity recommendations on a given column Azure SQL database using Piping.

```
Get-AzSqlDatabase -ResourceGroupName resourceGroup -ServerName server -DatabaseName database |  
Enable-AzSqlDatabaseSensitivityRecommendation -SchemaName schema
```

-TableName table -ColumnName column

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.sql/enable-azsqldatabasesensitivityrecommendation>

Learn more about Azure SQL Database data discovery and classification

<https://learn.microsoft.com/azure/sql-database/sql-database-data-discovery-and-classification>