



Windows PowerShell Get-Help on Cmdlet 'Enable-NetAdapter'

PS:\>Get-HELP Enable-NetAdapter -Full

NAME

Enable-NetAdapter

SYNOPSIS

Enables a network adapter.

SYNTAX

Enable-NetAdapter [-Name] <String[]> [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-IncludeHidden] [-PassThru] [-ThrottleLimit <Int32>] [-WhatIf]
[<CommonParameters>]

Enable-NetAdapter [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-IncludeHidden] -InterfaceDescription <String[]> [-PassThru] [-ThrottleLimit <Int32>] [-WhatIf]
[<CommonParameters>]

Enable-NetAdapter [-AsJob] [-CimSession <CimSession[]>] [-Confirm] -InputObject <CimInstance[]> [-PassThru] [-ThrottleLimit <Int32>] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The Enable-NetAdapter cmdlet enables a network adapter. A network adapter must be enabled to connect to a network.

PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete. The cmdlet immediately returns an object that

represents the job and then displays the command prompt. You can continue to work in the session while the job completes. To manage the job, use the ``*-Job``

cmdlets. To get the job results, use the Receive-Job (<https://go.microsoft.com/fwlink/?LinkID=113372>) cmdlet. For more information about Windows PowerShell

background jobs, see about_Jobs (<https://go.microsoft.com/fwlink/?LinkID=113251>).

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a New-CimSession

(<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or

[Get-CimSession](<https://go.microsoft.com/fwlink/p/?LinkId=227966>) cmdlet. The default is the current session on the local computer.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-IncludeHidden [<SwitchParameter>]

Indicates that the cmdlet includes both visible and hidden network adapters in the operation. By default only visible network adapters are included. If a wildcard

character is used in identifying a network adapter and this parameter has been specified, then the wildcard string is matched against both hidden and visible network adapters.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-InputObject <CimInstance[]>

Specifies the input to this cmdlet. You can use this parameter, or you can pipe the input to this cmdlet.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-InterfaceDescription <String[]>

Specifies an array of network adapter interface descriptions. For a physical network adapter this is typically the name

of the vendor of the network adapter

followed by a part number and description, such as `Contoso 12345 Gigabit Network Device`.

Required?	true
Position?	named
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-Name <String[]>

Specifies an array of network adapter names.

Required?	true
Position?	0
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-PassThru [<SwitchParameter>]

Returns an object representing the item with which you are working. By default, this cmdlet does not generate any output.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then

Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit

applies only to the current cmdlet, not to the session or to the computer.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Management.Infrastructure.CimInstance#ROOT/StandardCimv2/MSFT_NetAdapter[]

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the pound sign (`#`) provides the namespace and class name for the underlying WMI object.

OUTPUTS

Microsoft.Management.Infrastructure.CimInstance#ROOT/StandardCimv2/MSFT_NetAdapter

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management

Instrumentation (WMI) objects. The path after the

pound sign (`#`) provides the namespace and class name for the underlying WMI object.

NOTES

-- Example 1: Enable a network adapter by the specified name --

```
PS C:\> Enable-NetAdapter -Name "Ethernet 1"
```

This command is another version of the cmdlet that uses position and wildcard characters.

```
PS C:\> Enable-NetAdapter "E*2"
```

This command enables the network adapter named Ethernet 1 and restarts the network adapter.

Example 2: Enable a network adapter by the specified name on a remote computer

```
PS C:\> Enable-NetAdapter -Name "VMGuestTrafficAdapter" -CimSession "HyperVServer4"
```

This command enables the network adapter named VMGuestTrafficAdapter on the remote computer named HyperVServer4 and restarts the network adapter.

RELATED LINKS

Online

Version:

https://learn.microsoft.com/powershell/module/netadapter/enable-netadapter?view=windowsserver2022-ps&wt.mc_id=ps-gethelp

Disable-NetAdapter