



Windows PowerShell Get-Help on Cmdlet 'Enable-NetIPsecRule'

PS:\>Get-HELP Enable-NetIPsecRule -Full

NAME

Enable-NetIPsecRule

SYNOPSIS

Enables a previously disabled IPsec rule.

SYNTAX

```
Enable-NetIPsecRule [-All] [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru]
[-PolicyStore <String>] [-ThrottleLimit <Int32>]
[-TracePolicyStore] [-WhatIf] [<CommonParameters>]
```

```
Enable-NetIPsecRule [-AllowSetKey <Boolean[]>] [-AllowWatchKey <Boolean[]&;] [-AsJob] [-CimSession <CimSession[]>]
[-Confirm] [-Description <String[]>] [-DisplayGroup
<String[]>] [-Enabled {True | False}] [-EncryptedTunnelBypass <Boolean[]>] [-ForwardPathLifetime <UInt32[]>]
[-GPOSession <String>] [-Group <String[]>]
[-InboundSecurity {None | Request | Require}] [-KeyModule {Default | IKEv1 | AuthIP | IKEv2}] [-Machine <String[]>]
[-Mode {None | Tunnel | Transport}]
[-OutboundSecurity {None | Request | Require}] [-PassThru] [-Phase1AuthSet <String[]>] [-Phase2AuthSet <String[]>]
[-PolicyStore <String>] [-PolicyStoreSource
```

<String[]> [-PolicyStoreSourceType {None | Local | GroupPolicy | Dynamic | Generated | Hardcoded}] [-PrimaryStatus {Unknown | OK | Inactive | Error}]

[-QuickModeCryptoSet <String[]>] [-RemoteTunnelHostname <String[]>] [-RequireAuthorization <Boolean[]>] [-Status <String[]>] [-ThrottleLimit <Int32>]

[-TracePolicyStore] [-User <String[]>] [-WhatIf] [<CommonParameters>]

Enable-NetIPsecRule [-AsJob] -AssociatedNetFirewallAddressFilter <CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru]

[-PolicyStore <String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]

Enable-NetIPsecRule [-AsJob] -AssociatedNetFirewallInterfaceFilter <CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru]

[-PolicyStore <String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]

Enable-NetIPsecRule [-AsJob] -AssociatedNetFirewallInterfaceTypeFilter <CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru]

[-PolicyStore <String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]

Enable-NetIPsecRule [-AsJob] -AssociatedNetFirewallPortFilter <CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru] [-PolicyStore

<String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]

Enable-NetIPsecRule [-AsJob] -AssociatedNetFirewallProfile <CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru] [-PolicyStore

<String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]

Enable-NetIPsecRule [-AsJob] -AssociatedNetIPsecPhase1AuthSet <CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru] [-PolicyStore

<String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]

Enable-NetIPsecRule [-AsJob] -AssociatedNetIPsecPhase2AuthSet <CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru] [-PolicyStore

<String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]

```
Enable-NetIPsecRule [-AsJob] -AssociatedNetIPsecQuickModeCryptoSet <CimInstance> [-CimSession <CimSession[]>]
[-Confirm] [-GPOSession <String>] [-PassThru]
[-PolicyStore <String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]
```

```
Enable-NetIPsecRule [-AsJob] [-CimSession <CimSession[]>] [-Confirm] -DisplayName <String[]> [-GPOSession
<String>] [-PassThru] [-PolicyStore <String>]
[-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]
```

```
Enable-NetIPsecRule [-IPsecRuleName] <String[]> [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-GPOSession
<String>] [-PassThru] [-PolicyStore <String>]
[-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]
```

```
Enable-NetIPsecRule [-AsJob] [-CimSession <CimSession[]>] [-Confirm] -InputObject <CimInstance[]> [-PassThru]
[-ThrottleLimit <Int32>] [-WhatIf] [<CommonParameters>]
```

DESCRIPTION

The Enable-NetIPsecRule cmdlet enables a previously disabled IPsec rule to be active within the computer or a group policy organizational unit.

This cmdlet gets one or more IPsec rules to be enabled with the IPsecRuleName parameter (default), the DisplayName parameter, rule properties, or by associated

filters or objects. The Enabled parameter value for the resulting queried rules is set to True.

Enabling firewall and IPsec rules can be useful for debugging IPsec policy mismatch issues, but is easier when the rules are in the local, or persistent, store.

Enabling rules in a Group Policy Object (GPO) container will not take effect until the next time the client applies the GPO. To troubleshoot GPO-based IPsec policy,

consider copying all the rules, and authorization and cryptographic sets from the GPO to a computer that does not have the GPO policy applied using the corresponding

Copy-NetIPsecRule cmdlets. This is the way to locally modify the policy, in order to troubleshoot any IPsec failures.

PARAMETERS

-All [<SwitchParameter>]

Indicates that all of the IPsec rules within the specified policy store are enabled.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-AllowSetKey <Boolean[]>

Indicates that matching IPsec rules of the indicated value are enabled. This parameter specifies that the IPsec rule allows trusted intermediaries to override

keying material. If this parameter is set to True, then the trusted intermediaries are allowed to manipulate the cryptographic keying material used with an IPsec

security association (SA). It is possible that when this parameter is True at both ends, the computer will perform arbitration through SA negotiation so that one

end sets the key while the other end watches the key. See the AllowWatchKey parameter for more information. The default value is False. This parameter is only supported on Windows Server 2012.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-AllowWatchKey <Boolean[]>

Indicates that matching IPsec rules of the indicated value are enabled. This parameter specifies that the IPsec rule allows trusted intermediaries to provide

notification of changes in keying material. If this parameter is set to True, then the trusted intermediaries are allowed to retrieve the cryptographic keying

material associated with an IPsec security association (SA), and to subscribe for notification of changes. The default value is False. This parameter is only supported on Windows Server 2012.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-AssociatedNetFirewallAddressFilter <CimInstance>

Gets only the IPsec rules that are associated with the given address filter to be enabled. A NetFirewallAddressFilter object represents the address conditions associated with a rule. See the Get-NetFirewallAddressFilter cmdlet for more information.

Required?	true
Position?	named
Default value	None
Accept pipeline input?	True (ByValue)
Accept wildcard characters?	false

-AssociatedNetFirewallInterfaceFilter <CimInstance>

Gets the IPsec rules that are associated with the given interface filter to be enabled. A NetFirewallInterfaceFilter object represents the interface conditions

associated with a rule. See the Get-NetFirewallInterfaceFilter cmdlet for more information.

Required?	true
Position?	named
Default value	None
Accept pipeline input?	True (ByValue)
Accept wildcard characters?	false

-AssociatedNetFirewallInterfaceTypeFilter <CimInstance>

Gets the IPsec rules that are associated with the given interface type filter to be enabled. A NetFirewallInterfaceTypeFilter object represents the interface conditions associated with a rule. See the Get-NetFirewallInterfaceTypeFilter cmdlet for more information.

Required?	true
Position?	named
Default value	None
Accept pipeline input?	True (ByValue)
Accept wildcard characters?	false

-AssociatedNetFirewallPortFilter <CimInstance>

Gets the IPsec rules that are associated with the given port filter to be enabled. A NetFirewallPortFilter object represents the port conditions associated with a rule. See the Get-NetFirewallPortFilter cmdlet for more information.

Required?	true
Position?	named
Default value	None
Accept pipeline input?	True (ByValue)
Accept wildcard characters?	false

-AssociatedNetFirewallProfile <CimInstance>

Gets the IPsec rules that are associated with the given firewall profile type to be enabled. A NetFirewallProfile object represents the profile conditions

associated with a rule. See the Get-NetFirewallProfile cmdlet for more information.

Required?	true
Position?	named
Default value	None
Accept pipeline input?	True (ByValue)
Accept wildcard characters?	false

-AssociatedNetIPsecPhase1AuthSet <CimInstance>

Gets the IPsec rules that are associated with the given phase 1 authentication set to be enabled. A NetIPsecPhase1AuthSet object represents the phase 1 authorization set conditions associated with an IPsec or main mode rule. This parameter sets the methods for main mode negotiation by describing the proposals for computer authentication. See the Get-NetIPsecPhase1AuthSet cmdlet for more information. Alternatively, the Phase1AuthSet parameter can be used for the same purpose, but does not allow the authentication set to be piped into the cmdlet and the set must be specified with the IPsecRuleName parameter.

Required?	true
Position?	named
Default value	None
Accept pipeline input?	True (ByValue)
Accept wildcard characters?	false

-AssociatedNetIPsecPhase2AuthSet <CimInstance>

Gets the IPsec rules that are associated, via the pipeline, with the input phase 2 authentication set to be enabled. A NetIPsecPhase1AuthSet object represents the phase 2 authorization set conditions associated with a rule. See the Get-NetIPsecPhase2AuthSet cmdlet for more information. Alternatively, the Phase2AuthSet parameter can be used for the same purpose, but does not allow the authentication set to be piped into the cmdlet and the set must be specified with the IPsecRuleName parameter.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-AssociatedNetIPsecQuickModeCryptoSet <CimInstance>

Gets the IPsec rules that are associated, via the pipeline, with the input quick mode cryptographic set to be enabled. A NetIPsecQuickModeCryptoSet object

represents a quick mode cryptographic set that contains cryptographic proposals. This parameter specifies parameters for the quick mode negotiation as well as

dictating the cryptographic proposals that should be proposed during the exchange. This is only associated with IPsec rules. See the

Get-NetIPsecQuickModeCryptoSet cmdlet for more information. Alternatively, the QuickModeCryptoSet parameter can be used for the same purpose, but does not allow

the cryptographic set to be piped into the cmdlet and the set must be specified by the IPsecRuleName parameter.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a New-CimSession

(<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or

[Get-CimSession](<https://go.microsoft.com/fwlink/p/?LinkId=227966>)cmdlet. The default is the current session on the local computer.

Required? false
Position? named
Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-Description <String[]>

Specifies that matching IPsec rules of the indicated description are enabled. Wildcard characters are accepted. This parameter provides information about the

IPsec rule. This parameter specifies a localized, user-facing description of the object.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-DisplayGroup <String[]>

Specifies that only matching firewall rules of the indicated group association are enabled. Wildcard characters are accepted. The Group parameter specifies the

source string for this parameter. If the value for this parameter is a localizable string, then the Group parameter contains an indirect string. Rule groups can

be used to organize rules by influence and allows batch rule modifications. Using the Set-NetIPsecRule cmdlet, if the group name is specified for a set of rules

or sets, then all of the rules or sets in that group receive the same set of modifications. It is good practice to specify the Group parameter value with a

universal and world-ready indirect @FirewallAPI name. This parameter cannot be specified upon object creation using

the New-NetIPsecRule cmdlet, but can be

modified using dot-notation and the Set-NetIPsecRule cmdlet.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-DisplayName <String[]>

Specifies that only matching IPsec rules of the indicated display name are enabled. Wildcard characters are accepted.

Specifies the localized, user-facing name

of the IPsec rule being created. When creating a rule this parameter is required. This parameter value is locale-dependent. If the object is not modified, this

parameter value may change in certain circumstances. When writing scripts in multi-lingual environments, the IPsecRuleName parameter should be used instead, where

the default value is a randomly assigned value. This parameter cannot be set to All.

Required? true

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Enabled <Enabled[]>

Specifies that matching IPsec rules of the indicated state are enabled. This parameter specifies that the rule object is administratively enabled or

administratively enabled. The acceptable values for this parameter are:

- True: Specifies the rule is currently enabled.

- False: Specifies the rule is currently disabled.

A disabled rule will not actively modify computer behavior, but the management construct still exists on the computer so it can be re-enabled.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-EncryptedTunnelBypass <Boolean[]>

Indicates that matching IPsec rules of the specified value are enabled. This parameter specifies the encapsulation state for network traffic sent to a tunnel end

point that is already IPsec protected. If this parameter is set to True, then the network traffic sent to a tunnel end point that is already IPsec protected does

not have to be encapsulated again. This option can improve network performance in the case where network traffic that is already end-to-end protected by other

IPsec rules. The default value is False. This parameter is only supported on firstref_server_7 and Windows Server 2012.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-ForwardPathLifetime <UInt32[]>

Specifies that matching IPsec rules of the specified path lifetime value are enabled. This parameter specifies the session key lifetime for an IPsec rule, in

minutes. The acceptable values for this parameter are: 78 through 172799. The default value is 0 minutes. When managing a GPO, the default setting is

NotConfigured. This parameter is only supported on Windows Server 2012.

Required?	false
-----------	-------

Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-GPOSession <String>

Specifies the network GPO from which to retrieve the rules to be enabled. This parameter is used in the same way as the PolicyStore parameter. When modifying

GPOs in Windows PowerShell, each change to a GPO requires the entire GPO to be loaded, modified, and saved back. On a busy Domain Controller (DC), this can be a

slow and resource-heavy operation. A GPO Session loads a domain GPO onto the local computer and makes all changes in a batch, before saving it back. This reduces

the load on the DC and speeds up the Windows PowerShell cmdlets. To load a GPO Session, use the Open-NetGPO cmdlet. To save a GPO Session, use the Save-NetGPO cmdlet.

Required? false
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-Group <String[]>

Specifies that only matching IPsec rules of the indicated group association are enabled. Wildcard characters are accepted. This parameter specifies the source

string for the DisplayGroup parameter. If the DisplayGroup parameter value is a localizable string, then this parameter contains an indirect string. Rule groups

can be used to organize rules by influence and allows batch rule modifications. Using the Set-NetIPsecRule cmdlets, if the group name is specified for a set of

rules or sets, then all of the rules or sets in that group receive the same set of modifications. It is good practice to specify this parameter value with a

universal and world-ready indirect @FirewallAPI name. The DisplayGroup parameter cannot be specified upon object creation using the New-NetIPsecRule cmdlet, but

can be modified using dot-notation and the Set-NetIPsecRule cmdlet.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-IPsecRuleName <String[]>

Specifies an array of names of IPsec rules to enable. Wildcard characters are accepted.

Required?	true
Position?	0
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-InboundSecurity <SecurityPolicy[]>

Specifies that matching IPsec rules of the indicated security policy are enabled. This parameter determines the degree of enforcement for security on inbound traffic. The acceptable values for this parameter are:

- None: No authentication is requested or required for connections that match the rule. It specifies that the local computer does not attempt authentication for any network connections that match this rule. This option is typically used to grant IPsec exemptions for network connections that do not need to be protected by IPsec, but would otherwise match other rules that could cause the connection to be dropped.
- Request: Authentication is requested for connections that match the rule. The local computer attempts to authenticate any inbound network connections that match this rule, but allows the connection if the authentication attempt is no successful.
- Require: Authentication is required for connections that match the rule. If the authentication is not successful, then the inbound network traffic is discarded. The default value is None. When the OutboundSecurity parameter is also specified, the following

configurations are valid: InboundSecurity

\ OutboundSecurity = None\None, Request\None, Request\Request, Require\Request, or Require\Require.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-InputObject <CimInstance[]>

Specifies the input object that is used in a pipeline command.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-KeyModule <KeyModule[]>

Specifies that matching IPsec rules of the indicated key module are enabled. This parameter specifies which keying modules to negotiate. The acceptable values

for this parameter are: Default, AuthIP, IKEv1, or IKEv2.

- Default: Equivalent to both IKEv1 and AuthIP. Required in order for the rule to be applied to computers running Windows versions prior to nextref_server_7.

---- There are authorization and cryptographic methods that are only compatible with certain keying modules. This is a very advanced setting intended only for

specific interoperability scenarios. Overriding this parameter value may result in traffic being sent in plain-text if the authorization and cryptographic

settings are not supported by the keying modules there. - AuthIP: Supported with phase 2 authentication.

- IKEv1: Supported with pre-shared key (PSK), Certificates, and Kerberos.

- IKEv2: Not supported with Kerberos, PSK, or NTLM.

Windows versions prior to Windows Server 2012 only support the Default configuration.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-Machine <String[]>

Specifies that matching IPsec rules of the indicated computer accounts are enabled. This parameter specifies that only network packets that are authenticated as

incoming from or outgoing to a computer identified in the list of computer accounts (SID) match this rule. This parameter value is specified as an SDDL string.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-Mode <IPsecMode[]>

Specifies that matching IPsec rules of the indicated mode are enabled. This parameter specifies the type of IPsec mode connection that the IPsec rule defines.

The acceptable values for this parameter are: None, Transport, or Tunnel. The default value is Transport.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-OutboundSecurity <SecurityPolicy[]>

Specifies that matching IPsec rules of the indicated security policy are enabled. This parameter determines the degree of enforcement for security on outbound

traffic. The acceptable values for this parameter are:

- None: No authentication is requested or required for connections that match the rule. It specifies that the local computer does not attempt authentication for

any network connections that match this rule. This option is typically used to grant IPsec exemptions for network connections that do not need to be protected by

IPsec, but would otherwise match other rules that could cause the connection to be dropped. - Request: Authentication is requested for connections that match the

rule. The local computer attempts to authenticate any outbound network connections that match this rule, but allows the connection if the authentication attempt

fails. - Require: Authentication is required for connections that match the rule. If the authentication is not successful, then the outbound network traffic is

discarded.

The default value is None. When the InboundSecurity parameter is also specified, the following configurations are valid: InboundSecurity / OutboundSecurity =

None\None, Request\None, Request\Request, Require\Request, or Require\Require.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-PassThru [<SwitchParameter>]

Returns an object representing the item with which you are working. By default, this cmdlet does not generate any output.

Required? false

Position? named

Default value False
Accept pipeline input? False
Accept wildcard characters? false

`-Phase1AuthSet <String[]>`

Gets the IPsec rules that are associated with the given phase 1 authentication set to be enabled. A `NetIPsecPhase1AuthSet` object represents the phase 1

authorization set conditions associated with an IPsec or main mode rule. This parameter sets the methods for main mode negotiation by describing the proposals for

computer authentication. See the `Get-NetIPsecPhase1AuthSet` cmdlet for more information. Alternatively, the `Phase2AuthSet` parameter can be used for the same

purpose, but does not allow the authentication set to be piped into the cmdlet and the set must be specified with the `IPsecRuleName` parameter.

Required? false
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

`-Phase2AuthSet <String[]>`

Gets the IPsec rules that are associated with the given phase 2 authentication set to be enabled. A `NetIPsecPhase2AuthSet` object represents the phase 2

authorization set conditions associated with an IPsec or main mode rule. This parameter sets the methods for main mode negotiation by describing the proposals for

computer authentication. See the `Get-NetIPsecPhase2AuthSet` cmdlet for more information. Alternatively, the `Phase1AuthSet` parameter can be used for the same

purpose, but does not allow the authentication set to be piped into the cmdlet and the set must be specified with the `IPsecRuleName` parameter.

Required? false
Position? named
Default value None

Accept pipeline input? False

Accept wildcard characters? false

-PolicyStore <String>

Specifies the policy store from which to retrieve the rules to be enabled. A policy store is a container for firewall and IPsec policy. The acceptable values for this parameter are:

- PersistentStore: Sometimes called static rules, this store contains the persistent policy for the local computer. This policy is not from GPOs, and has been

created manually or programmatically (during application installation) on the computer. Rules created in this store are attached to the ActiveStore and activated

on the computer immediately. - ActiveStore: This store contains the currently active policy, which is the sum of all policy stores that apply to the computer.

This is the resultant set of policy (RSOP) for the local computer (the sum of all GPOs that apply to the computer), and the local stores (the PersistentStore, the

static Windows service hardening (WSH), and the configurable WSH). ---- GPOs are also policy stores. Computer GPOs can be specified as follows. -----

`-PolicyStore hostname`.

---- Active Directory GPOs can be specified as follows.

----- `-PolicyStore domain.fqdn.com\GPO_Friendly_Namedomain.fqdn.comGPO_Friendly_Name`.

----- Such as the following.

----- `-PolicyStore localhost`

----- `-PolicyStore corp.contoso.com\FirewallPolicy`

---- Active Directory GPOs can be created using the New-GPO cmdlet or the Group Policy Management Console. -

RSOP: This read-only store contains the sum of all

GPOs applied to the local computer.

- SystemDefaults: This read-only store contains the default state of firewall rules that ship with Windows Server 2012.
- StaticServiceStore: This read-only store contains all the service restrictions that ship with Windows Server 2012.

Optional and product-dependent features are considered part of Windows Server 2012 for the purposes of WFAS. -

ConfigurableServiceStore: This read-write store contains all the service restrictions that are added for third-party services. In addition, network isolation rules that are created for Windows Store application containers will appear in this policy store. The default value is PersistentStore. The Set-NetIPsecRule cmdlet cannot be used to add an object to a policy store. An object can only be added to a policy store at creation time with the Copy-NetIPsecRule cmdlet or with the New-NetIPsecRule cmdlet.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-PolicyStoreSource <String[]>

Specifies that IPsec rules matching the indicated policy store source are enabled. This parameter contains a path to the policy store where the rule originated if the object is retrieved from the ActiveStore with the TracePolicyStoreSource option set. This parameter value is automatically generated and should not be modified. The monitoring output from this parameter is not completely compatible with the PolicyStore parameter. This parameter value cannot always be passed into the PolicyStore parameter. Domain GPOs are one example in which this parameter contains only the GPO name, not the domain name.

Required?	false
Position?	named
Default value	None

Accept pipeline input? False

Accept wildcard characters? false

-PolicyStoreSourceType <PolicyStoreType[]>

Specifies that IPsec rules that match the indicated policy store source type are enabled. This parameter describes the type of policy store where the rule

originated if the object is retrieved from the ActiveStore with the TracePolicyStoreSource option set. This parameter value is automatically generated and should

not be modified. The acceptable values for this parameter are:

- Local: The object originates from the local store.

- GroupPolicy: The object originates from a GPO.

- Dynamic: The object originates from the local runtime state.

This policy store name is not valid for use in cmdlets, but may appear when monitoring active policy. - Generated: The object was generated automatically. This

policy store name is not valid for use in cmdlets, but may appear when monitoring active policy. - Hardcoded: The object was hard-coded. This policy store name

is not valid for use in cmdlets, but may appear when monitoring active policy.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-PrimaryStatus <PrimaryStatus[]>

Specifies that IPsec rules that match the indicated primary status are enabled. This parameter specifies the overall status of the rule.

- OK: Specifies that the rule will work as specified.

- Degraded: Specifies that one or more parts of the rule will not be enforced.
- Error: Specifies that the computer is unable to use the rule at all.

See the Status and StatusCode fields of the object for more detailed status information.

Required? false
 Position? named
 Default value None
 Accept pipeline input? False
 Accept wildcard characters? false

-QuickModeCryptoSet <String[]>

Specifies that matching IPsec rules of the specified quick mode cryptographic set are enabled. This parameter specifies the quick mode cryptographic set to be

associated with the IPsec rule. A NetIPsecMainModeCryptoSet object represents quick mode cryptographic conditions associated with an IPsec rule. This parameter

sets the methods for quick mode negotiation by describing the proposals for encryption. See the New-NetIPsecQuickModeCryptoSet cmdlet for more information.

Alternatively, the AssociatedNetIPsecQuickModeCryptoSet parameter can be used for the same purpose, but is used to pipe the input set into the rule. When

specifying cryptographic sets, the IPsecRuleName parameter value of the cryptographic set. The object cannot be directly passed to this cmdlet.

Required? false
 Position? named
 Default value None
 Accept pipeline input? False
 Accept wildcard characters? false

-RemoteTunnelHostname <String[]>

Specifies that matching IPsec rules of the specified second end point tunnel host name are enabled. Specifies a fully

qualified DNS name that resolves to a list

of remote tunnel end points. This parameter is only supported on Windows Server 2012. This parameter can only be used with multiple remote tunnel end points.

Specifying this parameter prevents a non-asymmetric tunnel mode IPsec rule from being created. Rule creation will fail when a single remote tunnel end point and

this parameter are specified, or when remote tunnel end point is Any and this parameter is specified.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-RequireAuthorization <Boolean[]>

Indicates that matching IPsec rules of the specified value are enabled. Specifies the given value for an IPsec rule. If this parameter is set to True, then

enforcement of authorization is allowed for end points. This parameter is only supported on nextref_server_7 and Windows Server 2012.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Status <String[]>

Specifies that IPsec rules that match the indicated status are enabled. This parameter describes the status message for the specified status code value. The

status code is a numerical value that indicates any syntax, parsing, or runtime errors in the rule or set. This parameter value should not be modified.

Required? false

Position? named

Default value None
Accept pipeline input? False
Accept wildcard characters? false

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then

Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet, not to the session or to the computer.

Required? false
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-TracePolicyStore [<SwitchParameter>]

Specifies that the name of the source GPO is queried and set to the PolicyStoreSource parameter value.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-User <String[]>

Specifies that matching IPsec rules of the indicated user accounts are enabled. This parameter specifies that only network packets that are authenticated as

incoming from or outgoing to a user identified in the list of user accounts match this rule. This parameter value is specified as an SDDL string.

Required? false

Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Management.Infrastructure.CimInstance#root\StandardCimv2\MSFT_NetAddressFilter

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the pound sign (`#`) provides the namespace and class name for the underlying WMI object.

Microsoft.Management.Infrastructure.CimInstance#root\StandardCimv2\MSFT_NetConSecRule[]

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the pound sign (`#`) provides the namespace and class name for the underlying WMI object.

Microsoft.Management.Infrastructure.CimInstance#root\StandardCimv2\MSFT_NetFirewallProfile

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management

Instrumentation (WMI) objects. The path after the

pound sign (`#`) provides the namespace and class name for the underlying WMI object.

Microsoft.Management.Infrastructure.CimInstance#root\StandardCimv2\MSFT_NetIKEP1AuthSet

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the

pound sign (`#`) provides the namespace and class name for the underlying WMI object.

Microsoft.Management.Infrastructure.CimInstance#root\StandardCimv2\MSFT_NetIKEP2AuthSet

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the

pound sign (`#`) provides the namespace and class name for the underlying WMI object.

Microsoft.Management.Infrastructure.CimInstance#root\StandardCimv2\MSFT_NetIKEQMCryptoSet

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the

pound sign (`#`) provides the namespace and class name for the underlying WMI object.

Microsoft.Management.Infrastructure.CimInstance#root\StandardCimv2\MSFT_NetInterfaceFilter

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the

pound sign (`#`) provides the namespace and class name for the underlying WMI object.

Microsoft.Management.Infrastructure.CimInstance#root\StandardCimv2\MSFT_NetInterfaceTypeFilter

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the

pound sign (`#`) provides the namespace and class name for the underlying WMI object.

Microsoft.Management.Infrastructure.CimInstance#root\StandardCimv2\MSFT_NetProtocolPortFilter

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the

pound sign (`#`) provides the namespace and class name for the underlying WMI object.

OUTPUTS

```
Microsoft.Management.Infrastructure.CimInstance#root\StandardCimv2\MSFT_NetConSecRule[]
```

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the

pound sign (`#`) provides the namespace and class name for the underlying WMI object.

NOTES

----- EXAMPLE 1 -----

```
PS C:\>Enable-NetIPsecRule -DisplayName "Require Outbound Authentication" -PolicyStore  
domain.contoso.com\gpo_name
```

This example enables an IPsec rule in a GPO by specifying the localized name.

----- EXAMPLE 2 -----

```
PS C:\>Enable-NetIPsecRule -Group "Ipsec-DirectAccess-Traffic" -Mode Transport -PolicyStore ActiveStore
```

This example enables all transport mode DA rules on the local computer.

----- EXAMPLE 3 -----

```
PS C:\>$Phase1AuthSet = Get-NetIPsecPhase1AuthSet -DisplayName "Computer Kerb, CA Auth"
```

```
PS C:\>Enable-NetIPsecRule -InputObject $Phase1AuthSet
```

This example enables the IPsec rules associated with the specified phase 1 authentication set.

RELATED LINKS

Online

Version:

https://learn.microsoft.com/powershell/module/netsecurity/enable-netipsecrule?view=windowsserver2022-ps&wt.mc_id=ps-gethelp

Copy-NetIPsecRule

Disable-NetIPsecRule

Get-NetFirewallAddressFilter

Get-NetFirewallInterfaceFilter

Get-NetFirewallInterfaceTypeFilter

Get-NetFirewallPortFilter

Get-NetFirewallProfile

Get-NetIPsecPhase1AuthSet

Get-NetIPsecPhase2AuthSet

Get-NetIPsecQuickModeCryptoSet

Get-NetIPsecRule

New-NetIPsecRule

Open-NetGPO

Remove-NetIPsecRule

Save-NetGPO

Set-NetIPsecRule