



Windows PowerShell Get-Help on Cmdlet 'Export-BCSecretKey'

PS:\>Get-HELP Export-BCSecretKey -Full

NAME

Export-BCSecretKey

SYNOPSIS

Exports a secret key to a file.

SYNTAX

Export-BCSecretKey [-Filename] <String> [-FilePassphrase] <String> [-AsJob] [-CimSession <CimSession[]>] [-Confirm]
[-Force] [-ThrottleLimit <Int32>] [-WhatIf]
[<CommonParameters>]

DESCRIPTION

The Export-BCSecretKey cmdlet exports a secret key to a file.

PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete.

The cmdlet immediately returns an object that represents the job and then displays the command prompt. You can continue to work in the session while the job

completes. To manage the job, use the ``*-Job`` cmdlets. To get the job results, use the `Receive-Job` (<https://go.microsoft.com/fwlink/?LinkID=113372>) cmdlet.

For more information about Windows PowerShell background jobs, see `about_Jobs` (<https://go.microsoft.com/fwlink/?LinkID=113251>).

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

`-CimSession <CimSession[]>`

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a `New-CimSession`

(<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or

`[Get-CimSession](https://go.microsoft.com/fwlink/p/?LinkId=227966)` cmdlet. The default is the current session on the local computer.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

`-Confirm [<SwitchParameter>]`

Prompts you for confirmation before running the cmdlet.

Required?	false
Position?	named

Default value False
Accept pipeline input? False
Accept wildcard characters? false

-FilePassphrase <String>

Specifies the passphrase for the file that contains the key information to be affected by this cmdlet.

Required? true
Position? 2
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-Filename <String>

Specifies the path of the file to be affected by this cmdlet.

Required? true
Position? 1
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-Force [<SwitchParameter>]

Forces the command to run without asking for user confirmation.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is

omitted or a value of `0` is entered, then

Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet, not to the session or to the computer.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

`-WhatIf [<SwitchParameter>]`

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

`<CommonParameters>`

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see `about_CommonParameters` (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

None

OUTPUTS

None

NOTES

----- Example 1: Export the secret key -----

```
PS C:\> Export-BCSecretKey -Filename "C:\share1\secretkey.key" -FilePassphrase "mySecretPhrase"
```

This command exports the secret key to the file C:\share1\secretkey.key with the passphrase mySecretPhrase.

RELATED LINKS

Online

Version:

https://learn.microsoft.com/powershell/module/branchcache/export-bcsecretkey?view=windowsserver2022-ps&wt.mc_id=ps-gethelp

Import-BCSecretKey

Set-BCSecretKey