



Windows PowerShell Get-Help on Cmdlet 'Get-AzADApplication'

PS:\>Get-HELP Get-AzADApplication -Full

NAME

Get-AzADApplication

SYNOPSIS

Lists entities from applications or get entity from applications by key

SYNTAX

```
Get-AzADApplication [-Select <String[]>] [-Count] [-Filter <String>] [-OrderBy <String[]>] [-Search <String>]
[-ConsistencyLevel <String>] [-First <UInt64>] [-Skip
<UInt64>] [-AppendSelected] [-DefaultProfile <PSObject>] [-CountVariable <String>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

```
Get-AzADApplication -ObjectId <String> [-Select <String[]>] [-First <UInt64>] [-Skip <UInt64>] [-AppendSelected]
[-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

Get-AzADApplication -OwnedApplication [-Select <String[]>] [-Orderby <String[]>] [-First <UInt64>] [-Skip <UInt64>]
[-AppendSelected] [-DefaultProfile <PSObject>]

[-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>]
[-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]

Get-AzADApplication [-Select <String[]>] -DisplayNameStartWith <String> [-First <UInt64>] [-Skip <UInt64>]
[-AppendSelected] [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]

Get-AzADApplication [-Select <String[]>] -DisplayName <String> [-First <UInt64>] [-Skip <UInt64>] [-AppendSelected]
[-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]

Get-AzADApplication [-Select <String[]>] -ApplicationId <Guid> [-First <UInt64>] [-Skip <UInt64>] [-AppendSelected]
[-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]

Get-AzADApplication [-Select <String[]>] -IdentifierUri <String> [-First <UInt64>] [-Skip <UInt64>] [-AppendSelected]
[-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]

Lists entities from applications or get entity from applications by key

PARAMETERS

-ObjectId <String>

key: id of application

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-OwnedApplication [<SwitchParameter>]

get owned application

Required? true

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Select <String[]>

Select properties to be returned

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Count [<SwitchParameter>]

Include count of items

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Filter <String>

Filter items by property values, for more detail about filter query please see:

<https://learn.microsoft.com/en-us/graph/filter-query-parameter>

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-OrderBy <String[]>

Order items by property values

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Search <String>

Search items by search phrases

Required? false
Position? named
Default value
Accept pipeline input? false

Accept wildcard characters? false

-DisplayNameStartWith <String>

application display name starts with

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DisplayName <String>

application display name

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ApplicationId <Guid>

application id

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IdentifierUri <String>

application identifier uri

Required? true

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ConsistencyLevel <String>

Indicates the requested consistency level.

Documentation URL:

<https://developer.microsoft.com/en-us/office/blogs/microsoft-graph-advanced-queries-for-directory-objects-are-now-generally-available/>

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-First <UInt64>

Gets only the first 'n' objects.

Required? false
Position? named
Default value 0
Accept pipeline input? false
Accept wildcard characters? false

-Skip <UInt64>

Ignores the first 'n' objects and then gets the remaining objects.

Required? false
Position? named
Default value 0
Accept pipeline input? false

Accept wildcard characters? false

-AppendSelected [<SwitchParameter>]

Append properties selected with default properties when this switch is on, only works with parameter '-Select'.

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-CountVariable <String>

Specifies a count of the total number of items in a collection.

By default, this variable will be set in the global scope.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Resources.MSGraph.Models.ApiV10.IMicrosoftGraphApplication

----- EXAMPLE 1 -----

----- EXAMPLE 2 -----

```
PS C:\>Get-AzADApplication -First 10
```

----- EXAMPLE 3 -----

```
PS C:\>Get-AzADApplication -DisplayNameStartsWith $prefix
```

----- EXAMPLE 4 -----

```
PS C:\>Get-AzADApplication -ObjectId $id -Select Tags -AppendSelected
```

----- EXAMPLE 5 -----

```
PS C:\>Get-AzADApplication -OwnedApplication
```

----- EXAMPLE 6 -----

```
PS C:\>Get-AzADApplication -Filter "startsWith(DisplayName,'some-name')"
```

----- EXAMPLE 7 -----

```
PS C:\>Get-AzADApplication -First 10 -ConsistencyLevel eventual -Count -CountVariable 'result'
```

```
$result
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.resources/get-azadapplication>