



Windows PowerShell Get-Help on Cmdlet 'Get-AzAksCluster'

PS:\>Get-HELP Get-AzAksCluster -Full

NAME

Get-AzAksCluster

SYNOPSIS

List Kubernetes managed clusters.

SYNTAX

```
Get-AzAksCluster [-Id] <System.String> [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-SubscriptionId
<System.String>] [<CommonParameters>]
```

```
Get-AzAksCluster [-ResourceGroupName] <System.String> [-Name] <System.String> [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-SubscriptionId
<System.String>] [<CommonParameters>]
```

```
Get-AzAksCluster [[-ResourceGroupName] <System.String>] [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
[-SubscriptionId <System.String>] [<CommonParameters>]
```

DESCRIPTION

List Kubernetes managed clusters.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Id <System.String>

Id of a managed Kubernetes cluster

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Name <System.String>

Name of your managed Kubernetes cluster

Required? true

Position? 1

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-ResourceGroupName <System.String>

Resource group name

Required? false

Position? 0

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-SubscriptionId <System.String>

The ID of the subscription. By default, cmdlets are executed in the subscription that is set in the current context. If the user specifies another subscription,

the current cmdlet is executed in the subscription specified by the user. Overriding subscriptions only take effect during the lifecycle of the current cmdlet. It

does not change the subscription in the context, and does not affect subsequent cmdlets.

Required? false

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

System.String

OUTPUTS

Microsoft.Azure.Commands.Aks.Models.PSKubernetesCluster

NOTES

----- List all Kubernetes clusters -----

Get-AzAksCluster

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.aks/get-azakscluster>