



Windows PowerShell Get-Help on Cmdlet 'Get-AzApiManagementAuthorizationServerClientSecret'

PS:\>Get-HELP Get-AzApiManagementAuthorizationServerClientSecret -Full

NAME

Get-AzApiManagementAuthorizationServerClientSecret

SYNOPSIS

Gets an API Management authorization server client secret.

SYNTAX

```

Get-AzApiManagementAuthorizationServerClientSecret [-Context
<Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext> [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ServerId
<System.String>] [<CommonParameters>]

```

```

Get-AzApiManagementAuthorizationServerClientSecret [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
    -ResourceId <System.String> [-ServerId <System.String>] [<CommonParameters>]

```

DESCRIPTION

The Get-AzApiManagementAuthorizationServerClientSecret cmdlet gets the client secret of the Azure API Management

authorization server.

PARAMETERS

-Context <Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext>

Instance of PsApiManagementContext. This parameter is required.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName, ByValue)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-ResourceId <System.String>

Arm Resource Identifier of the authorization server. If specified will try to find authorization server by the identifier. This parameter is required.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ServerId <System.String>

Identifier of the authorization server. If specified will find authorization server by the identifier. This parameter is optional.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext

System.String

OUTPUTS

Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementClientSecret

NOTES

Example 1: Get a specified authorization server client secret by id

```
$ApiMgmtContext = New-AzApiManagementContext -ResourceGroupName "Api-Default-WestUS" -ServiceName  
"contoso"
```

```
Get-AzApiManagementAuthorizationServerClientSecret -Context $ApiMgmtContext -ServerId "0123456789"
```

This command gets the specified authorization server client secret.

RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.apimanagement/get-azapimanagementauthorizationserverclientsecret>