



Windows PowerShell Get-Help on Cmdlet 'Get-AzApiManagementNamedValue'

PS:\>Get-HELP Get-AzApiManagementNamedValue -Full

NAME

Get-AzApiManagementNamedValue

SYNOPSIS

Gets a list or a particular Named Value.

SYNTAX

```

Get-AzApiManagementNamedValue -Context
<Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext> [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Name
    <System.String>] [<CommonParameters>]

```

```

Get-AzApiManagementNamedValue -Context
<Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext> [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-NamedValueId
    <System.String>] [<CommonParameters>]

```

```

Get-AzApiManagementNamedValue -Context
<Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext> [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Name
    <System.String>] [<CommonParameters>]

```

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Tag
<System.String>] [<CommonParameters>]

DESCRIPTION

The Get-AzApiManagementNamedValue cmdlet gets a list or a particular named value. Value will not be included into result details if the named value marked as a secret. To get secret value, use Get-AzApiManagementNamedValueSecretValue .

PARAMETERS

-Context <Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext>

Instance of PsApiManagementContext. This parameter is required.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName, ByValue)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Name <System.String>

Finds named values with names containing the string Name. This parameter is optional.

Required? false

Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-NamedValueId <System.String>

Identifier of the named value. If specified will try to find named value by the identifier. This parameter is optional.

Required? false
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Tag <System.String>

Finds named values associated with a Tag. If specified will return all properties associated with a tag. This parameter is optional.

Required? false
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext

System.String

OUTPUTS

Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementNamedValue

NOTES

----- Example 1: Get Named Value by name -----

```
$apimContext = New-AzApiManagementContext -ResourceGroupName "Api-Default-WestUS" -ServiceName "contoso"  
Get-AzApiManagementNamedValue -Context $apimContext -Name "sql-connectionstring"
```

This command gets the named value details given the named value name.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.apimanagement/get-azapimanagementnamedvalue>