



Windows PowerShell Get-Help on Cmdlet 'Get-AzApiManagementOpenIdConnectProvider'

PS:\>Get-HELP Get-AzApiManagementOpenIdConnectProvider -Full

NAME

Get-AzApiManagementOpenIdConnectProvider

SYNOPSIS

Gets OpenID Connect providers.

SYNTAX

Get-AzApiManagementOpenIdConnectProvider -Context

<Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext> [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Name

<System.String>] [<CommonParameters>]

Get-AzApiManagementOpenIdConnectProvider -Context

<Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext> [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]

[-OpenIdConnectProviderId <System.String>] [<CommonParameters>]

The `Get-AzApiManagementOpenIdConnectProvider` cmdlet gets OpenID Connect providers in Azure API Management. ClientSecret will not be included into result details. To get client secret, use `Get-AzApiManagementOpenIdConnectProviderClientSecret`.

PARAMETERS

`-Context <Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext>`

Specifies a `PsApiManagementContext` object.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName, ByValue)

Accept wildcard characters? false

`-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>`

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

`-Name <System.String>`

Specifies a friendly name of a provider. If you specify a name, this cmdlet gets that provider.

Required? false

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-OpenIdConnectProviderId <System.String>

Specifies an ID of the provider that this cmdlet removes. If you specify an ID, this cmdlet gets that provider.

Required? false

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext

System.String

OUTPUTS

Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementOpenIdConnectProvider

NOTES

----- Example 1: Get all providers -----

```
$apimContext = New-AzApiManagementContext -ResourceGroupName "Api-Default-WestUS" -ServiceName "contoso"  
Get-AzApiManagementOpenIdConnectProvider -Context $apimContext
```

This command gets all OpenID Connect providers for the specified context.

----- Example 2: Get a provider by using an ID -----

```
$apimContext = New-AzApiManagementContext -ResourceGroupName "Api-Default-WestUS" -ServiceName "contoso"  
Get-AzApiManagementOpenIdConnectProvider -Context $apimContext -OpenIdConnectProviderId "OICProvider01"
```

This command gets the provider that has the ID OICProvider01.

----- Example 3: Get a provider by using a name -----

```
$apimContext = New-AzApiManagementContext -ResourceGroupName "Api-Default-WestUS" -ServiceName "contoso"  
Get-AzApiManagementOpenIdConnectProvider -Context $apimContext -Name "Contoso OpenID Connect Provider"
```

This command gets the provider named Contoso OpenID Connect Provider.

RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.apimanagement/get-azapimanagementopenidconnectprovider>

New-AzApiManagementOpenIdConnectProvider

Remove-AzApiManagementOpenIdConnectProvider

Set-AzApiManagementOpenIdConnectProvider

