



Windows PowerShell Get-Help on Cmdlet 'Get-AzApiManagementOpenIdConnectProviderClientSecret'

PS:\>Get-HELP Get-AzApiManagementOpenIdConnectProviderClientSecret -Full

NAME

Get-AzApiManagementOpenIdConnectProviderClientSecret

SYNOPSIS

Gets OpenID Connect provider client secret.

SYNTAX

Get-AzApiManagementOpenIdConnectProviderClientSecret -Context

<Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext>

[-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]

-OpenIdConnectProviderId <System.String>

[<CommonParameters>]

DESCRIPTION

Gets OpenID Connect provider client secret.

-Context <Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext>

Instance of PsApiManagementContext. This parameter is required.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName, ByValue)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-OpenIdConnectProviderId <System.String>

Identifier of a OpenID Connect Provider. This parameter is required.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext

System.String

OUTPUTS

Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementClientSecret

NOTES

---- Example 1: Get a provider client secret by using an ID ----

```
$apimContext = New-AzApiManagementContext -ResourceGroupName "Api-Default-WestUS" -ServiceName "contoso"
Get-AzApiManagementOpenIdConnectProviderClientSecret -Context $apimContext -OpenIdConnectProviderId
"OICProvider01"
```

This command gets a client secret of the provider that has the ID OICProvider01.

RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.apimanagement/get-azapimanagementopenidconnectproviderclientsecret>

