



Windows PowerShell Get-Help on Cmdlet 'Get-AzAppConfigurationDeletedStore'

PS:\>Get-HELP Get-AzAppConfigurationDeletedStore -Full

NAME

Get-AzAppConfigurationDeletedStore

SYNOPSIS

Gets a deleted Azure app configuration store.

SYNTAX

```
Get-AzAppConfigurationDeletedStore [-SubscriptionId <String[]>] [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
    <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

```
Get-AzAppConfigurationDeletedStore -Location <String> -Name <String> [-SubscriptionId <String[]>] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend
    <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzAppConfigurationDeletedStore -InputObject <IAppConfigurationIdentity> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
```

[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]

DESCRIPTION

Gets a deleted Azure app configuration store.

PARAMETERS

-Location <String>

The location in which uniqueness will be verified.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <String>

The name of the configuration store.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String[]>

The Microsoft Azure subscription ID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IAppConfigurationIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.AppConfiguration.Models.IAppConfigurationIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.AppConfiguration.Models.Api20220501.IDeletedConfigurationStore

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IAppConfigurationIdentity>: Identity Parameter

[ConfigStoreName <String>]: The name of the configuration store.

[GroupName <String>]: The name of the private link resource group.

[Id <String>]: Resource identity path

[KeyValueName <String>]: Identifier of key and label combination. Key and label are joined by \$ character. Label is optional.

[Location <String>]: The location in which uniqueness will be verified.

[PrivateEndpointConnectionName <String>]: Private endpoint connection name

[ResourceGroupName <String>]: The name of the resource group to which the container registry belongs.

[SubscriptionId <String>]: The Microsoft Azure subscription ID.

----- EXAMPLE 1 -----

```
PS C:\>Remove-AzAppConfigurationStore -Name azptestappstore -ResourceGroupName azptest-gp
```

```
Get-AzAppConfigurationDeletedStore
```

----- EXAMPLE 2 -----

```
PS C:\>Remove-AzAppConfigurationStore -Name azptestappstore -ResourceGroupName azptest-gp
```

```
Get-AzAppConfigurationDeletedStore -Location eastus -Name azptestappstore
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.appconfiguration/get-azappconfigurationdeletedstore>

