



## ***Windows PowerShell Get-Help on Cmdlet 'Get-AzAppConfigurationStore'***

***PS: \>Get-HELP Get-AzAppConfigurationStore -Full***

### NAME

Get-AzAppConfigurationStore

### SYNOPSIS

Get or list app configuration stores.

### SYNTAX

```
Get-AzAppConfigurationStore [-SubscriptionId <String[]>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

```
Get-AzAppConfigurationStore -Name <String> -ResourceGroupName <String> [-SubscriptionId <String[]>]
[-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzAppConfigurationStore -ResourceGroupName <String> [-SubscriptionId <String[]>] [-DefaultProfile <PSObject>]
[-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
```

[ -HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]  
[-ProxyUseDefaultCredentials] [<CommonParameters>]

Get-AzAppConfigurationStore -InputObject <IAppConfigurationIdentity> [-DefaultProfile <PSObject>] [-Break]  
[-HttpPipelineAppend <SendAsyncStep[]>]  
[ -HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]  
[-ProxyUseDefaultCredentials] [<CommonParameters>]

## DESCRIPTION

Get or list app configuration stores.

## PARAMETERS

-Name <String>

The name of the configuration store.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group to which the container registry belongs.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String[]>

The Microsoft Azure subscription ID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -InputObject <IAppConfigurationIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

#### -DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value            False

Accept pipeline input?    false

Accept wildcard characters? false

#### -HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required?                false

Position?                named

Default value

Accept pipeline input?    false

Accept wildcard characters? false

#### -HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required?                false

Position?                named

Default value

Accept pipeline input?    false

Accept wildcard characters? false

#### -Proxy <Uri>

The URI for the proxy server to use

Required?                false

Position?                named

Default value

Accept pipeline input?    false

Accept wildcard characters? false

#### -ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

**-ProxyUseDefaultCredentials [<SwitchParameter>]**

Use the default credentials for the proxy

Required? false  
Position? named  
Default value False  
Accept pipeline input? false  
Accept wildcard characters? false

**<CommonParameters>**

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

**INPUTS**

Microsoft.Azure.PowerShell.Cmdlets.AppConfiguration.Models.IAppConfigurationIdentity

**OUTPUTS**

Microsoft.Azure.PowerShell.Cmdlets.AppConfiguration.Models.Api20220501.IConfigurationStore

**NOTES**

## COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about\_Hash\_Tables.

INPUTOBJECT <IAppConfigurationIdentity>: Identity Parameter

[ConfigStoreName <String>]: The name of the configuration store.

[GroupName <String>]: The name of the private link resource group.

[Id <String>]: Resource identity path

[KeyValueName <String>]: Identifier of key and label combination. Key and label are joined by \$ character. Label is optional.

[Location <String>]: The location in which uniqueness will be verified.

[PrivateEndpointConnectionName <String>]: Private endpoint connection name

[ResourceGroupName <String>]: The name of the resource group to which the container registry belongs.

[SubscriptionId <String>]: The Microsoft Azure subscription ID.

### ----- EXAMPLE 1 -----

```
PS C:\>Get-AzAppConfigurationStore
```

### ----- EXAMPLE 2 -----

```
PS C:\>Get-AzAppConfigurationStore -ResourceGroupName azptest_gp
```

----- EXAMPLE 3 -----

```
PS C:\>Get-AzAppConfigurationStore -Name azptest-appstore -ResourceGroupName azptest_gp
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.appconfiguration/get-azappconfigurationstore>