



## ***Windows PowerShell Get-Help on Cmdlet 'Get-AzAutomanageConfigProfile'***

***PS: \>Get-HELP Get-AzAutomanageConfigProfile -Full***

### NAME

Get-AzAutomanageConfigProfile

### SYNOPSIS

Get information about a configuration profile

### SYNTAX

```
Get-AzAutomanageConfigProfile [-SubscriptionId <String[]>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

```
Get-AzAutomanageConfigProfile -Name <String> -ResourceGroupName <String> [-SubscriptionId <String[]>]
[-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzAutomanageConfigProfile -ResourceGroupName <String> [-SubscriptionId <String[]>] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
```

[ -HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]  
[-ProxyUseDefaultCredentials] [<CommonParameters>]

Get-AzAutomanageConfigProfile -InputObject <IAutomanageIdentity> [-DefaultProfile <PSObject>] [-Break]  
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend  
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]  
[<CommonParameters>]

## DESCRIPTION

Get information about a configuration profile

## PARAMETERS

-Name <String>

The configuration profile name.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String[]>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IAutomanageIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position?                named  
Default value            False  
Accept pipeline input?    false  
Accept wildcard characters? false

**-HttpPipelineAppend <SendAsyncStep[]>**

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required?                false  
Position?                named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

**-HttpPipelinePrepend <SendAsyncStep[]>**

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required?                false  
Position?                named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

**-Proxy <Uri>**

The URI for the proxy server to use

Required?                false  
Position?                named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

**-ProxyCredential <PSCredential>**

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

#### <CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

## INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Automanage.Models.IAutomanageIdentity

## OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Automanage.Models.Api20220504.IConfigurationProfile

## NOTES

## COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about\_Hash\_Tables.

INPUTOBJECT <IAutomanageIdentity>: Identity Parameter

[BestPracticeName <String>]: The Automanage best practice name.

[ClusterName <String>]: The name of the Arc machine.

[ConfigurationProfileAssignmentName <String>]: Name of the configuration profile assignment. Only default is supported.

[ConfigurationProfileName <String>]: Name of the configuration profile.

[Id <String>]: Resource identity path

[MachineName <String>]: The name of the Arc machine.

[ReportName <String>]: The report name.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SubscriptionId <String>]: The ID of the target subscription.

[VMName <String>]: The name of the virtual machine.

[VersionName <String>]: The Automanage best practice version name.

----- EXAMPLE 1 -----

```
PS C:\>Get-AzAutomanageConfigProfile
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzAutomanageConfigProfile -ResourceGroupName automangerg
```

----- EXAMPLE 3 -----

```
PS C:\>Get-AzAutomanageConfigProfile -ResourceGroupName automangerg -Name lucas-best-practices-devtest
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.automanage/get-azautomanageconfigprofile>