



Windows PowerShell Get-Help on Cmdlet 'Get-AzAutomationWebhook'

PS: \>Get-HELP Get-AzAutomationWebhook -Full

NAME

Get-AzAutomationWebhook

SYNOPSIS

Gets webhooks from Automation.

SYNTAX

```
Get-AzAutomationWebhook [-ResourceGroupName] <System.String> [-AutomationAccountName] <System.String>
[-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Name
<System.String> [<CommonParameters>]
```

```
Get-AzAutomationWebhook [-ResourceGroupName] <System.String> [-AutomationAccountName] <System.String>
[-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -RunbookName
<System.String> [<CommonParameters>]
```

DESCRIPTION

The Get-AzAutomationWebhook cmdlet gets webhooks. To get specific webhooks, specify a webhook name or specify the name of an Azure Automation runbook to get the

webhooks connected to it.
 Note: The WebhookUri is returned as empty string due to security concerns. Please make sure to save the webhook URL that

New-AzAutomationWebhook cmdlet returns, because it cannot be retrieved by using Get-AzAutomationWebhook .

PARAMETERS

-AutomationAccountName <System.String>

Specifies the name of an Automation account in which this cmdlet gets a webhook.

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Name <System.String>

Specifies the name of the webhook that this cmdlet gets.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ResourceGroupName <System.String>

Specifies the name of the resource group for which this cmdlet gets webhooks.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-RunbookName <System.String>

Specifies the name of a runbook for which this cmdlet gets webhooks.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

System.String

OUTPUTS

Microsoft.Azure.Commands.Automation.Model.Webhook

NOTES

----- Example 1: Get all webhooks for a runbook -----

```
Get-AzAutomationWebhook -RunbookName "Runbook03" -ResourceGroupName "ResourceGroup01"  
-AutomationAccountName "AutomationAccount01"
```

This command gets all webhooks for a runbook named Runbook03 in the Automation account named AutomationAccount01 in the resource group named ResourceGroup01.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.automation/get-azautomationwebhook>

New-AzAutomationWebhook

Remove-AzAutomationWebhook

Set-AzAutomationWebhook