



Windows PowerShell Get-Help on Cmdlet 'Get-AzCdnCustomDomain'

PS:\>Get-HELP Get-AzCdnCustomDomain -Full

NAME

Get-AzCdnCustomDomain

SYNOPSIS

Gets an existing custom domain within an endpoint.

SYNTAX

```
Get-AzCdnCustomDomain -EndpointName <String> -ProfileName <String> -ResourceGroupName <String>
[-SubscriptionId <String[]>] [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

```
Get-AzCdnCustomDomain -EndpointName <String> -Name <String> -ProfileName <String> -ResourceGroupName
<String> [-SubscriptionId <String[]>] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy
<Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzCdnCustomDomain -InputObject <ICdnIdentity> [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend
    <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

DESCRIPTION

Gets an existing custom domain within an endpoint.

PARAMETERS

-EndpointName <String>

Name of the endpoint under the profile which is unique globally.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <String>

Name of the custom domain within an endpoint.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProfileName <String>

Name of the CDN profile which is unique within the resource group.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

Name of the Resource group within the Azure subscription.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String[]>

Azure Subscription ID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <ICdnIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,
OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Cdn.Models.ICdnIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Cdn.Models.Api20240201.ICustomDomain

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <ICdnIdentity>: Identity Parameter

[CustomDomainName <String>]: Name of the domain under the profile which is unique globally.

[EndpointName <String>]: Name of the endpoint under the profile which is unique globally.

[Id <String>]: Resource identity path

[OriginGroupName <String>]: Name of the origin group which is unique within the endpoint.

[OriginName <String>]: Name of the origin which is unique within the profile.

[ProfileName <String>]: Name of the Azure Front Door Standard or Azure Front Door Premium which is unique within the resource group.

[ResourceGroupName <String>]: Name of the Resource group within the Azure subscription.

[RouteName <String>]: Name of the routing rule.

[RuleName <String>]: Name of the delivery rule which is unique within the endpoint.

[RuleSetName <String>]: Name of the rule set under the profile which is unique globally.

[SecretName <String>]: Name of the Secret under the profile.

[SecurityPolicyName <String>]: Name of the security policy under the profile.

[SubscriptionId <String>]: Azure Subscription ID.

----- EXAMPLE 1 -----

```
PS C:\>Get-AzCdnCustomDomain -ResourceGroupName testps-rg-da16jm -ProfileName cdn001 -EndpointName  
endptest001
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzCdnCustomDomain -ResourceGroupName testps-rg-da16jm -ProfileName cdn001 -EndpointName  
endptest001 -Name customdomain001
```

----- EXAMPLE 3 -----

```
PS C:\>New-AzCdnCustomDomain -ResourceGroupName testps-rg-da16jm -ProfileName cdn001 -EndpointName  
endptest001 -Name customdomain010 -HostName  
'testcm.dev.cdn.azure.cn' | Get-AzCdnCustomDomain
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.cdn/get-azcdncustomdomain>