



Windows PowerShell Get-Help on Cmdlet 'Get-AzCloudServiceRoleInstance'

PS:\>Get-HELP Get-AzCloudServiceRoleInstance -Full

NAME

Get-AzCloudServiceRoleInstance

SYNOPSIS

Gets a role instance from a cloud service.

SYNTAX

```
Get-AzCloudServiceRoleInstance -CloudServiceName <String> -ResourceGroupName <String> [-SubscriptionId
<String[]>] [-Expand <InstanceViewTypes>] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy
<Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzCloudServiceRoleInstance -CloudServiceName <String> -ResourceGroupName <String> -RoleInstanceName
<String> [-SubscriptionId <String[]>] [-Expand
<InstanceViewTypes>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>]
[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzCloudServiceRoleInstance -InputObject <ICloudServiceIdentity> [-Expand <InstanceViewTypes>] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend
    <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

DESCRIPTION

Gets a role instance from a cloud service.

PARAMETERS

-CloudServiceName <String>

Name of the cloud service.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

Name of the resource group.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-RoleInstanceName <String>

Name of the role instance.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String[]>

Subscription credentials which uniquely identify Microsoft Azure subscription.

The subscription ID forms part of the URI for every service call.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <ICloudServiceIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Expand <InstanceViewTypes>

The expand expression to apply to the operation.

'UserData' is not supported for cloud services.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.CloudService.Models.ICloudServiceIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.CloudService.Models.Api20220904.IRoleInstance

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

[about_Hash_Tables](#).

INPUTOBJECT <ICloudServiceIdentity>: Identity Parameter

[CloudServiceName <String>]: Name of the cloud service.

[IPConfigurationName <String>]: The IP configuration name.

[Id <String>]: Resource identity path

[Location <String>]: Name of the location that the OS version pertains to.

[NetworkInterfaceName <String>]: The name of the network interface.

[OSFamilyName <String>]: Name of the OS family.

[OSVersionName <String>]: Name of the OS version.

[PublicIPAddressName <String>]: The name of the public IP Address.

[ResourceGroupName <String>]: Name of the resource group.

[RoleInstanceName <String>]: Name of the role instance.

[RoleName <String>]: Name of the role.

[SubscriptionId <String>]: Subscription credentials which uniquely identify Microsoft Azure subscription. The subscription ID forms part of the URI for every service call.

[UpdateDomain <Int32?>]: Specifies an integer value that identifies the update domain. Update domains are identified with a zero-based index: the first update domain has an ID of 0, the second has an ID of 1, and so on.

----- EXAMPLE 1 -----

```
PS C:\>Get-AzCloudServiceRoleInstance -ResourceGroupName "ContosOrg" -CloudServiceName "ContosoCS"
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzCloudServiceRoleInstance -ResourceGroupName "ContosOrg" -CloudServiceName "ContosoCS"
-RoleInstanceName "ContosoFrontEnd_IN_0"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.cloudservice/get-azcloudserviceroleinstance>

