



### *Windows PowerShell Get-Help on Cmdlet 'Get-AzDataBricksWorkspace'*

***PS: \>Get-HELP Get-AzDataBricksWorkspace -Full***

#### NAME

Get-AzDataBricksWorkspace

#### SYNOPSIS

Gets the workspace.

#### SYNTAX

```
Get-AzDataBricksWorkspace [-SubscriptionId <String[]>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend  
<SendAsyncStep[]>] [-HttpPipelinePrepend  
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]  
[<CommonParameters>]
```

```
Get-AzDataBricksWorkspace -Name <String> -ResourceGroupName <String> [-SubscriptionId <String[]>] [-DefaultProfile  
<PSObject>] [-Break] [-HttpPipelineAppend  
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]  
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzDataBricksWorkspace -ResourceGroupName <String> [-SubscriptionId <String[]>] [-DefaultProfile <PSObject>]  
[-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
```

[ -HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]  
[-ProxyUseDefaultCredentials] [<CommonParameters>]

Get-AzDatabricksWorkspace -InputObject <IDatabricksIdentity> [-DefaultProfile <PSObject>] [-Break]  
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend  
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]  
[<CommonParameters>]

## DESCRIPTION

Gets the workspace.

## PARAMETERS

-Name <String>

The name of the workspace.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### `-SubscriptionId <String[]>`

The ID of the target subscription.

Required?                false

Position?                named

Default value

Accept pipeline input?    false

Accept wildcard characters? false

#### `-InputObject <IDataBricksIdentity>`

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required?                true

Position?                named

Default value

Accept pipeline input?    true (ByValue)

Accept wildcard characters? false

#### `-DefaultProfile <PSObject>`

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required?                false

Position?                named

Default value

Accept pipeline input?    false

Accept wildcard characters? false

#### `-Break [<SwitchParameter>]`

Wait for .NET debugger to attach

Required?                false

Position?                  named  
Default value              False  
Accept pipeline input?    false  
Accept wildcard characters? false

**-HttpPipelineAppend <SendAsyncStep[]>**

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required?                  false  
Position?                  named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

**-HttpPipelinePrepend <SendAsyncStep[]>**

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required?                  false  
Position?                  named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

**-Proxy <Uri>**

The URI for the proxy server to use

Required?                  false  
Position?                  named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

**-ProxyCredential <PSCredential>**

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

#### <CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about\\_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

## INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Databricks.Models.IDatabricksIdentity

## OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Databricks.Models.Api20230201.IWorkspace

## NOTES

## COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about\_Hash\_Tables.

INPUTOBJECT <IDatabricksIdentity>: Identity Parameter

[ConnectorName <String>]: The name of the azure databricks accessConnector.

[GroupId <String>]: The name of the private link resource

[Id <String>]: Resource identity path

[PeeringName <String>]: The name of the workspace vNet peering.

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SubscriptionId <String>]: The ID of the target subscription.

[WorkspaceName <String>]: The name of the workspace.

### ----- EXAMPLE 1 -----

```
PS C:\>Get-AzDatabricksWorkspace -ResourceGroupName azps_test_gp_db -Name azps-databricks-workspace-t3
```

### ----- EXAMPLE 2 -----

```
PS C:\>Get-AzDatabricksWorkspace
```

----- EXAMPLE 3 -----

```
PS C:\>Get-AzDatabricksWorkspace -ResourceGroupName azps_test_gp_db
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.databricks/get-azdatabrickswspace>