



Windows PowerShell Get-Help on Cmdlet 'Get-AzDnsForwardingRulesetForwardingRule'

PS:\>Get-HELP Get-AzDnsForwardingRulesetForwardingRule -Full

NAME

Get-AzDnsForwardingRulesetForwardingRule

SYNOPSIS

Gets properties of a forwarding rule in a DNS forwarding ruleset.

SYNTAX

```
Get-AzDnsForwardingRulesetForwardingRule -DnsForwardingRulesetName <String> -ResourceGroupName <String>
[-SubscriptionId <String[]>] [-Top <Int32>] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy
<Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzDnsForwardingRulesetForwardingRule -DnsForwardingRulesetName <String> -Name <String>
-ResourceGroupName <String> [-SubscriptionId <String[]>] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy
<Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```

Get-AzDnsForwardingRulesetForwardingRule -InputObject <IDnsResolverIdentity> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
        [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]

```

DESCRIPTION

Gets properties of a forwarding rule in a DNS forwarding ruleset.

PARAMETERS

-DnsForwardingRulesetName <String>

The name of the DNS forwarding ruleset.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <String>

The name of the forwarding rule.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String[]>

The ID of the target subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <IDnsResolverIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true
Position? named
Default value
Accept pipeline input? true (ByValue)
Accept wildcard characters? false

-Top <Int32>

The maximum number of results to return.

If not specified, returns up to 100 results.

Required? false
Position? named
Default value 0
Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.DnsResolver.Models.IDnsResolverIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.DnsResolver.Models.Api20220701.IForwardingRule

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run `Get-Help`

`about_Hash_Tables`.

INPUTOBJECT <IDnsResolverIdentity>: Identity Parameter

[DnsForwardingRulesetName <String>]: The name of the DNS forwarding ruleset.

[DnsResolverName <String>]: The name of the DNS resolver.

[ForwardingRuleName <String>]: The name of the forwarding rule.

[Id <String>]: Resource identity path

[InboundEndpointName <String>]: The name of the inbound endpoint for the DNS resolver.

[OutboundEndpointName <String>]: The name of the outbound endpoint for the DNS resolver.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SubscriptionId <String>]: The ID of the target subscription.

[VirtualNetworkLinkName <String>]: The name of the virtual network link.

[VirtualNetworkName <String>]: The name of the virtual network.

----- EXAMPLE 1 -----

```
PS C:\>Get-AzDnsForwardingRulesetForwardingRule -DnsForwardingRulesetName DnsResolverName  
-ResourceGroupName sampleRG
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzDnsForwardingRulesetForwardingRule -DnsForwardingRulesetName DnsResolverName  
-ResourceGroupName sampleRG -Name forwardingRule
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.dnsresolver/get-azdnsforwardingrulesetforwardingrule>