



Windows PowerShell Get-Help on Cmdlet 'Get-AzEventGridNamespaceTopic'

PS:\>Get-HELP Get-AzEventGridNamespaceTopic -Full

NAME

Get-AzEventGridNamespaceTopic

SYNOPSIS

Get properties of a namespace topic.

SYNTAX

```
Get-AzEventGridNamespaceTopic -NamespaceName <String> -ResourceGroupName <String> [-SubscriptionId
<String[]>] [-Filter <String>] [-Top <Int32>] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy
<Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzEventGridNamespaceTopic -NamespaceName <String> -ResourceGroupName <String> [-SubscriptionId
<String[]>] -TopicName <String> [-DefaultProfile <PSObject>]
[-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>]
[-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```

Get-AzEventGridNamespaceTopic -TopicName <String> -NamespaceInputObject <IEventGridIdentity> [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend
    <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]

```

```

Get-AzEventGridNamespaceTopic -InputObject <IEventGridIdentity> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
    <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]

```

DESCRIPTION

Get properties of a namespace topic.

PARAMETERS

-NamespaceName <String>

Name of the namespace.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group within the user's subscription.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String[]>

Subscription credentials that uniquely identify a Microsoft Azure subscription.

The subscription ID forms part of the URI for every service call.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-TopicName <String>

Name of the namespace topic.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IEventGridIdentity>

Identity Parameter

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-NamespaceInputObject <IEventGridIdentity>

Identity Parameter

Required? true

Position? named
Default value
Accept pipeline input? true (ByValue)
Accept wildcard characters? false

-Filter <String>

The query used to filter the search results using OData syntax.

Filtering is permitted on the 'name' property only and with limited number of OData operations.

These operations are: the 'contains' function as well as the following logical operations: not, and, or, eq (for equal), and ne (for not equal).

No arithmetic operations are supported.

The following is a valid filter example: \$filter=contains(name, 'PATTERN') and name ne 'PATTERN-1'.

The following is not a valid filter example: \$filter=location eq 'westus'.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Top <Int32>

The number of results to return per page for the list operation.

Valid range for top parameter is 1 to 100.

If not specified, the default number of results to be returned is 20 items per page.

Required? false
Position? named
Default value 0
Accept pipeline input? false
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,

OutBuffer, PipelineVariable, and OutVariable. For more information, see

about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.EventGrid.Models.IEventGridIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.EventGrid.Models.INamespaceTopic

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IEventGridIdentity>: Identity Parameter

[CaCertificateName <String>]: Name of the CA certificate.

[ChannelName <String>]: Name of the channel.

[ClientGroupName <String>]: Name of the client group.

[ClientName <String>]: Name of the client.

[DomainName <String>]: Name of the domain.

[DomainTopicName <String>]: Name of the topic.

[EventSubscriptionName <String>]: Name of the event subscription.

[Id <String>]: Resource identity path

[Location <String>]: Name of the location.

[NamespaceName <String>]: Name of the namespace.

[ParentName <String>]: The name of the parent resource (namely, either, the topic name, domain name, or partner namespace name or namespace name).

[ParentType <String>]: The type of the parent resource. This can be either 'topics', 'domains', or

'\partnerNamespaces\' or '\namespaces\'.

[PartnerDestinationName <String>]: Name of the partner destination.

[PartnerNamespaceName <String>]: Name of the partner namespace.

[PartnerRegistrationName <String>]: Name of the partner registration.

[PartnerTopicName <String>]: Name of the partner topic.

[PermissionBindingName <String>]: Name of the permission binding.

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection connection.

[PrivateLinkResourceName <String>]: The name of private link resource will be either topic, domain, partnerNamespace or namespace.

[ProviderNamespace <String>]: Namespace of the provider of the topic.

[ResourceGroupName <String>]: The name of the resource group within the user's subscription.

[ResourceName <String>]: Name of the resource.

[ResourceTypeName <String>]: Name of the resource type.

[Scope <String>]: The scope of the event subscription. The scope can be a subscription, or a resource group, or a top level resource belonging to a resource

provider namespace, or an EventGrid topic. For example, use '/subscriptions/{subscriptionId}' for a subscription, '/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}' for a resource group, and

'/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}/providers/{resourceProviderNamespace}/{resourceType}/{resourceName}' for a resource, and

'/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}/providers/Microsoft.EventGrid/topics/{topicName}' for an EventGrid topic.

[SubscriptionId <String>]: Subscription credentials that uniquely identify a Microsoft Azure subscription. The subscription ID forms part of the URI for every service call.

[SystemTopicName <String>]: Name of the system topic.

[TopicName <String>]: Name of the domain topic.

[TopicSpaceName <String>]: Name of the Topic space.

[TopicTypeName <String>]: Name of the topic type.

[VerifiedPartnerName <String>]: Name of the verified partner.

[CaCertificateName <String>]: Name of the CA certificate.

[ChannelName <String>]: Name of the channel.

[ClientGroupName <String>]: Name of the client group.

[ClientName <String>]: Name of the client.

[DomainName <String>]: Name of the domain.

[DomainTopicName <String>]: Name of the topic.

[EventSubscriptionName <String>]: Name of the event subscription.

[Id <String>]: Resource identity path

[Location <String>]: Name of the location.

[NamespaceName <String>]: Name of the namespace.

[ParentName <String>]: The name of the parent resource (namely, either, the topic name, domain name, or partner namespace name or namespace name).

[ParentType <String>]: The type of the parent resource. This can be either 'topics', 'domains', or 'partnerNamespaces' or 'namespaces'.

[PartnerDestinationName <String>]: Name of the partner destination.

[PartnerNamespaceName <String>]: Name of the partner namespace.

[PartnerRegistrationName <String>]: Name of the partner registration.

[PartnerTopicName <String>]: Name of the partner topic.

[PermissionBindingName <String>]: Name of the permission binding.

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection connection.

[PrivateLinkResourceName <String>]: The name of private link resource will be either topic, domain, partnerNamespace or namespace.

[ProviderNamespace <String>]: Namespace of the provider of the topic.

[ResourceGroupName <String>]: The name of the resource group within the user's subscription.

[ResourceName <String>]: Name of the resource.

[ResourceTypeName <String>]: Name of the resource type.

[Scope <String>]: The scope of the event subscription. The scope can be a subscription, or a resource group, or a top level resource belonging to a resource

provider namespace, or an EventGrid topic. For example, use '/subscriptions/{subscriptionId}' for a subscription,

'/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}' for a resource group, and

'/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}/providers/{resourceProviderNamespace}/{resourceType}/{resourceName}' for a resource, and

'/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}/providers/Microsoft.EventGrid/topics/{topicName}' for an EventGrid topic.

[SubscriptionId <String>]: Subscription credentials that uniquely identify a Microsoft Azure subscription. The subscription ID forms part of the URI for every service call.

[SystemTopicName <String>]: Name of the system topic.

[TopicName <String>]: Name of the domain topic.

[TopicSpaceName <String>]: Name of the Topic space.

[TopicTypeName <String>]: Name of the topic type.

[VerifiedPartnerName <String>]: Name of the verified partner.

----- EXAMPLE 1 -----

```
PS C:\>Get-AzEventGridNamespaceTopic -NamespaceName azps-eventgridnamespace -ResourceGroupName azps_test_group_eventgrid
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzEventGridNamespaceTopic -NamespaceName azps-eventgridnamespace -ResourceGroupName azps_test_group_eventgrid -TopicName azps-topic
```

----- EXAMPLE 3 -----

```
PS C:\>$namespace = Get-AzEventGridNamespace -ResourceGroupName azps_test_group_eventgrid -Name  
azps-eventgridnamespace
```

```
Get-AzEventGridNamespaceTopic -NamespaceInputObject $namespace -TopicName azps-topic
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.eventgrid/get-azeventgridnamespacetopic>