



Windows PowerShell Get-Help on Cmdlet 'Get-AzFunctionApp'

PS:\>Get-HELP Get-AzFunctionApp -Full

NAME

Get-AzFunctionApp

SYNOPSIS

Gets function apps in a subscription.

SYNTAX

```
Get-AzFunctionApp [-SubscriptionId <String[]>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>]
```

```
[-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzFunctionApp [-SubscriptionId <String[]>] -Location <String> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

```
Get-AzFunctionApp [-SubscriptionId <String[]>] -ResourceGroupName <String> -Name <String> [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
Page 1/12
```

[-ProxyUseDefaultCredentials] [<CommonParameters>]

Get-AzFunctionApp [-SubscriptionId <String[]>] -ResourceGroupName <String> [-IncludeSlot] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]

DESCRIPTION

Gets function apps in a subscription.

PARAMETERS

-SubscriptionId <String[]>

The Azure subscription ID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Location <String>

The location of the function app.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Name <String>

The name of the function app.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-IncludeSlot [<SwitchParameter>]

Use to specify whether to include deployment slots in results.

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-DefaultProfile <PSObject>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-HttpPipelineAppend <SendAsyncStep[]>

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-HttpPipelinePrepend <SendAsyncStep[]>

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-Proxy <Uri>

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-ProxyCredential <PSCredential>

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Functions.Models.Api20190801.ISite

----- EXAMPLE 1 -----

```
PS C:\>Get-AzFunctionApp
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzFunctionApp -ResourceGroupName Functions-West-Europe-Win -Name Functions1-Windows-DoNet
```

----- EXAMPLE 3 -----

```
PS C:\>Get-AzFunctionApp -ResourceGroupName Functions-West-Europe-Win
```

----- EXAMPLE 4 -----

```
PS C:\>Get-AzFunctionApp -SubscriptionId fe16564a-d943-4bf8-8c28-cf01708c3f8b
```

----- EXAMPLE 5 -----

```
PS C:\>Get-AzFunctionApp -Location "Central US"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.functions/get-azfunctionapp>