



Windows PowerShell Get-Help on Cmdlet 'Get-AzHealthcareFhirService'

PS:\>Get-HELP Get-AzHealthcareFhirService -Full

NAME

Get-AzHealthcareFhirService

SYNOPSIS

Gets the properties of the specified FHIR Service.

SYNTAX

```
Get-AzHealthcareFhirService -ResourceGroupName <String> [-SubscriptionId <String[]>] -WorkspaceName <String>
[-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]

[<CommonParameters>]
```

```
Get-AzHealthcareFhirService -Name <String> -ResourceGroupName <String> [-SubscriptionId <String[]>]
-WorkspaceName <String> [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]

[<CommonParameters>]
```

```

Get-AzHealthcareFhirService -InputObject <IHealthcareApisIdentity> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
    <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]

```

DESCRIPTION

Gets the properties of the specified FHIR Service.

PARAMETERS

-Name <String>

The name of FHIR Service resource.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group that contains the service instance.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String[]>

The subscription identifier.

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-WorkspaceName <String>

The name of workspace resource.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <IHealthcareApisIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true
Position? named
Default value
Accept pipeline input? true (ByValue)
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.HealthcareApis.Models.IHealthcareApisIdentity

OUTPUTS

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IHealthcareApisIdentity>: Identity Parameter

[DicomServiceName <String>]: The name of DICOM Service resource.

[FhirDestinationName <String>]: The name of IoT Connector FHIR destination resource.

[FhirServiceName <String>]: The name of FHIR Service resource.

[GroupName <String>]: The name of the private link resource group.

[Id <String>]: Resource identity path

[IotConnectorName <String>]: The name of IoT Connector resource.

[LocationName <String>]: The location of the operation.

[OperationResultId <String>]: The ID of the operation result to get.

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection associated with the Azure resource

[ResourceGroupName <String>]: The name of the resource group that contains the service instance.

[ResourceName <String>]: The name of the service instance.

[SubscriptionId <String>]: The subscription identifier.

[WorkspaceName <String>]: The name of workspace resource.

----- EXAMPLE 1 -----

```
PS C:\>Get-AzHealthcareFhirService -ResourceGroupName azps_test_group -WorkspaceName azpshcws
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzHealthcareFhirService -Name azpsfhirservice -ResourceGroupName azps_test_group -WorkspaceName  
azpshcws
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.healthcareapis/get-azhealthcarefhirservice>