



Windows PowerShell Get-Help on Cmdlet 'Get-AzKeyVaultCertificateContact'

PS: \>Get-HELP Get-AzKeyVaultCertificateContact -Full

NAME

Get-AzKeyVaultCertificateContact

SYNOPSIS

Gets contacts that are registered for certificate notifications for a key vault.

SYNTAX

Get-AzKeyVaultCertificateContact [-InputObject] <Microsoft.Azure.Commands.KeyVault.Models.PSKeyVault>

[-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]

[<CommonParameters>]

Get-AzKeyVaultCertificateContact [-ResourceId] <System.String> [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]

[<CommonParameters>]

Get-AzKeyVaultCertificateContact [-VaultName] <System.String> [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]

[<CommonParameters>]

DESCRIPTION

The Get-AzKeyVaultCertificateContact cmdlet gets contacts that are registered for certificate notifications for a key vault in Azure Key Vault.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-InputObject <Microsoft.Azure.Commands.KeyVault.Models.PSKeyVault>

KeyVault object.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-ResourceId <System.String>

KeyVault Id.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-VaultName <System.String>

Specifies the name of the key vault.

Required? true

Position? 0

Default value None

Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.KeyVault.Models.PSKeyVault

System.String

OUTPUTS

Microsoft.Azure.Commands.KeyVault.Models.PSKeyVaultCertificateContact

NOTES

----- Example 1: Get all certificate contacts -----

```
$Contacts = Get-AzKeyVaultCertificateContact -VaultName "Contoso"
```

Email	VaultName
-----	-----
username@microsoft.com	Contoso
username1@microsoft.com	Contoso

This command gets all of the contacts for the certificate objects in the Contoso key vault, and then stores them in the \$Contacts variable.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.keyvault/get-azkeyvaultcertificatecontact>

Add-AzKeyVaultCertificateContact

Remove-AzKeyVaultCertificateContact