



Windows PowerShell Get-Help on Cmdlet 'Get-AzManagedServicesDefinition'

PS:\>Get-HELP Get-AzManagedServicesDefinition -Full

NAME

Get-AzManagedServicesDefinition

SYNOPSIS

Gets the registration definition details.

SYNTAX

```
Get-AzManagedServicesDefinition [-Scope <String>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

```
Get-AzManagedServicesDefinition -Name <String> [-Scope <String>] [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

```
Get-AzManagedServicesDefinition -InputObject <IManagedServicesIdentity> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
```

[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]

DESCRIPTION

Gets the registration definition details.

PARAMETERS

-Name <String>

The GUID of the registration definition.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Scope <String>

The scope of the resource.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IManagedServicesIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.ManagedServices.Models.IManagedServicesIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.ManagedServices.Models.Api20200201Preview.IRegistrationDefinition

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IManagedServicesIdentity>: Identity Parameter

[Id <String>]: Resource identity path

[MarketplaceIdentifier <String>]: The Azure Marketplace identifier. Expected formats: {publisher}.{product[-preview]}.{planName}.{version} or {publisher}.{product[-preview]}.{planName} or {publisher}.{product[-preview]} or {publisher}.

[RegistrationAssignmentId <String>]: The GUID of the registration assignment.

[RegistrationDefinitionId <String>]: The GUID of the registration definition.

[Scope <String>]: The scope of the resource.

----- EXAMPLE 1 -----

```
PS C:\>Get-AzManagedServicesDefinition
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzManagedServicesDefinition -Name xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxxx |Format-List -Property Id,
Name, Type, ManagedByTenantId, Authorization,
EligibleAuthorization
```

----- EXAMPLE 3 -----

```
PS C:\>Get-AzManagedServicesDefinition -Scope /subscriptions/xxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxxx | Format-List
-Property Id, Name, Type, ManagedByTenantId,
Authorization, EligibleAuthorization
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.managedservices/get-azmanagedservicesdefinition>