



Windows PowerShell Get-Help on Cmdlet 'Get-AzPostgreSqlConfiguration'

PS:\>Get-HELP Get-AzPostgreSqlConfiguration -Full

NAME

Get-AzPostgreSqlConfiguration

SYNOPSIS

Gets information about a configuration of server.

SYNTAX

```
Get-AzPostgreSqlConfiguration -ResourceGroupName <String> -ServerName <String> [-SubscriptionId <String[]>]
[-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzPostgreSqlConfiguration -Name <String> -ResourceGroupName <String> -ServerName <String> [-SubscriptionId
<String[]>] [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

Get-AzPostgreSqlConfiguration -InputObject <IPostgreSqlIdentity> [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
 <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]

DESCRIPTION

Gets information about a configuration of server.

PARAMETERS

-Name <String>

The name of the server configuration.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ServerName <String>

The name of the server.

Required? true

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String[]>

The ID of the target subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <IPostgreSqlIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true
Position? named
Default value
Accept pipeline input? true (ByValue)
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

`-ProxyCredential <PSCredential>`

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

`-ProxyUseDefaultCredentials [<SwitchParameter>]`

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

`<CommonParameters>`

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.PostgreSql.Models.IPostgreSqlIdentity

OUTPUTS

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IPostgreSqlIdentity>: Identity Parameter

[ConfigurationName <String>]: The name of the server configuration.

[DatabaseName <String>]: The name of the database.

[FirewallRuleName <String>]: The name of the server firewall rule.

[Id <String>]: Resource identity path

[LocationName <String>]: The name of the location.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SecurityAlertPolicyName <SecurityAlertPolicyName?>]: The name of the security alert policy.

[ServerName <String>]: The name of the server.

[SubscriptionId <String>]: The ID of the target subscription.

[VirtualNetworkRuleName <String>]: The name of the virtual network rule.

----- EXAMPLE 1 -----

```
PS C:\>Get-AzPostgreSqlConfiguration -ResourceGroupName PostgreSqlTestRG -ServerName PostgreSqlTestServer
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzPostgreSqlConfiguration -Name timezone -ResourceGroupName PostgreSqlTestRG -ServerName  
PostgreSqlTestServer
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.postgresql/get-azpostgresqlconfiguration>