



Windows PowerShell Get-Help on Cmdlet 'Get-AzPostgreSqlFlexibleServerDatabase'

PS:\>Get-HELP Get-AzPostgreSqlFlexibleServerDatabase -Full

NAME

Get-AzPostgreSqlFlexibleServerDatabase

SYNOPSIS

Gets information about a database.

SYNTAX

Get-AzPostgreSqlFlexibleServerDatabase -ResourceGroupName <String> -ServerName <String> [-SubscriptionId <String>] [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep>] [-HttpPipelinePrepend <SendAsyncStep>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]

[<CommonParameters>]

Get-AzPostgreSqlFlexibleServerDatabase -Name <String> -ResourceGroupName <String> -ServerName <String> [-SubscriptionId <String>] [-DefaultProfile <PSObject>]

[-Break] [-HttpPipelineAppend <SendAsyncStep>] [-HttpPipelinePrepend <SendAsyncStep>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [<CommonParameters>]

```
Get-AzPostgreSqlFlexibleServerDatabase -InputObject <IPostgreSqlIdentity> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

DESCRIPTION

Gets information about a database.

PARAMETERS

-Name <String>

The name of the database.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ServerName <String>

The name of the server.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String[]>

The ID of the target subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <IPostgreSqlIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true
Position? named
Default value
Accept pipeline input? true (ByValue)
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.PostgreSql.Models.IPostgreSqlIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.PostgreSql.Models.Api20210601.IDatabaseAutoGenerated

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IPostgreSqlIdentity>: Identity Parameter

[ConfigurationName <String>]: The name of the server configuration.

[DatabaseName <String>]: The name of the database.

[FirewallRuleName <String>]: The name of the server firewall rule.

[Id <String>]: Resource identity path

[LocationName <String>]: The name of the location.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SecurityAlertPolicyName <SecurityAlertPolicyName?>]: The name of the security alert policy.

[ServerName <String>]: The name of the server.

[SubscriptionId <String>]: The ID of the target subscription.

[VirtualNetworkRuleName <String>]: The name of the virtual network rule.

----- EXAMPLE 1 -----

```
PS C:\>Get-AzPostgreSqlFlexibleServerDatabase -ResourceGroupName PowershellPostgreSqlTest -ServerName postgresql-test
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzPostgreSqlFlexibleServerDatabase -ResourceGroupName PowershellPostgreSqlTest -ServerName
postgresql-test -Name flexibleserverdb
```

----- EXAMPLE 3 -----

```
PS C:\>Get-AzPostgreSqlFlexibleServerDatabase -InputObject
/subscriptions/0000000000-0000-0000-0000-000000000000/resourceGroups/PowershellPostgreSqlTest/providers/Micr
osoft.DBforPostgreSQL/flexibleServers/postgresql-test/databases/flexibleserverdb
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.postgresql/get-azpostgresqlflexibleserverdatabase>