



Windows PowerShell Get-Help on Cmdlet 'Get-AzRecoveryServicesAsrvCenter'

PS: \>Get-HELP Get-AzRecoveryServicesAsrvCenter -Full

NAME

Get-AzRecoveryServicesAsrvCenter

SYNOPSIS

Gets details of the vCenter servers registered for discovery on the Configuration server specified by the ASR fabric.

SYNTAX

```
Get-AzRecoveryServicesAsrvCenter [-DefaultProfile  
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Fabric  
<Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRFabric> [<CommonParameters>]
```

```
Get-AzRecoveryServicesAsrvCenter [-DefaultProfile  
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Fabric  
    <Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRFabric> -Name <System.String>  
[<CommonParameters>]
```

```
Get-AzRecoveryServicesAsrvCenter [-DefaultProfile  
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -ResourceId  
    <System.String> [<CommonParameters>]
```

DESCRIPTION

The `Get-AzRecoveryServicesAsrvCenter` cmdlet gets details of the vCenter servers registered for discovery on the Configuration server specified by the ASR fabric.

PARAMETERS

`-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>`

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

`-Fabric <Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRFabric>`

ASR fabric object representing the Configuration Server.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

`-Name <System.String>`

Name of the vCenter server.

Required? true

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-ResourceId <System.String>

Specifies the resourceId of vCenter.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

System.String

Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRFabric

OUTPUTS

Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRvCenter

NOTES

----- Example 1 -----

Get-AzRecoveryServicesAsrvCenter -Fabric \$Fabric -Name \$Name

FriendlyName : inctest81
Server : 10.150.209.27
Port : 443
Name : inctest81
ID :
/Subscriptions/xxxxxxxxxx/resourceGroups/canaryexproute/providers/Microsoft.RecoveryServices/vaults/xxxxxxxxxx/replicationFabrics/xxxxxxxxxx
xxxx/replicationvCenters/inctest81
FabricArmResourceName : d011a5abf48190235963ee3a88ad188ee6bca8a4c6cd0c8d7ce5d439aa77ffd9
ProcessServerId : 526C9B6C-4039-D841-97A92FB0BD153B53
AccountId : 2
DiscoveryStatus : Pending
LastHeartbeat :

Get azure site recovery vCenter by fabric name and name of vCenter.

----- Example 2 -----

Get-AzRecoveryServicesAsrvCenter -Fabric \$Fabric

Get azure site recovery vCenter list by fabric name.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.recoveryservices/get-azrecoveryservicesasrvcenter>

