



Windows PowerShell Get-Help on Cmdlet 'Get-AzRoleAssignmentScheduleInstance'

PS: \>Get-HELP Get-AzRoleAssignmentScheduleInstance -Full

NAME

Get-AzRoleAssignmentScheduleInstance

SYNOPSIS

Gets the specified role assignment schedule instance.

SYNTAX

```
Get-AzRoleAssignmentScheduleInstance -Scope <String> [-Filter <String>] [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzRoleAssignmentScheduleInstance -Name <String> -Scope <String> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzRoleAssignmentScheduleInstance -InputObject <IAuthorizationIdentity> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
```

[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]

DESCRIPTION

Gets the specified role assignment schedule instance.

PARAMETERS

-Name <String>

The name (hash of schedule name + time) of the role assignment schedule to get.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Scope <String>

The scope of the role assignments schedules.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IAuthorizationIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Filter <String>

The filter to apply on the operation.

Use \$filter=atScope() to return all role assignment schedules at or above the scope.

Use \$filter=principalId eq {id} to return all role assignment schedules at, above or below the scope for the specified principal.

Use \$filter=assignedTo('{userId}') to return all role assignment schedule instances for the user.

Use \$filter=asTarget() to return all role assignment schedule instances created for the current user.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Resources.Authorization.Models.IAuthorizationIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Resources.Authorization.Models.Api20201001Preview.IRoleAssignmentScheduleInstance

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IAuthorizationIdentity>: Identity Parameter

[Id <String>]: Resource identity path

[RoleAssignmentScheduleInstanceName <String>]: The name (hash of schedule name + time) of the role assignment schedule to get.

[RoleAssignmentScheduleName <String>]: The name (guid) of the role assignment schedule to get.

[RoleAssignmentScheduleRequestName <String>]: The name of the role assignment to create. It can be any valid GUID.

[RoleEligibilityScheduleInstanceName <String>]: The name (hash of schedule name + time) of the role eligibility schedule to get.

[RoleEligibilityScheduleName <String>]: The name (guid) of the role eligibility schedule to get.

[RoleEligibilityScheduleRequestName <String>]: The name of the role eligibility to create. It can be any valid GUID.

[RoleManagementPolicyAssignmentName <String>]: The name of format {guid_guid} the role management policy assignment to get.

[RoleManagementPolicyName <String>]: The name (guid) of the role management policy to get.

[Scope <String>]: The scope of the role management policy.

----- EXAMPLE 1 -----

```
PS C:\>$scope = "/subscriptions/38ab2ccc-3747-4567-b36b-9478f5602f0d"
```

```
Get-AzRoleAssignmentScheduleInstance -Scope $scope
```

----- EXAMPLE 2 -----

PS C:\>\$scope = "/" # "/" stands for tenant level resource

Get-AzRoleAssignmentScheduleInstance -Scope \$scope -Filter "asTarget()"

----- EXAMPLE 3 -----

PS C:\>\$scope = "/subscriptions/38ab2ccc-3747-4567-b36b-9478f5602f0d"

\$filter = "roleDefinitionId eq '/providers/Microsoft.Authorization/roleDefinitions/8e3af657-a8ff-443c-a75c-2fe8c4bcb635'"

Get-AzRoleAssignmentScheduleInstance -Scope \$scope -Filter \$filter

----- EXAMPLE 4 -----

PS C:\>\$scope = "/subscriptions/38ab2ccc-3747-4567-b36b-9478f5602f0d"

Get-AzRoleAssignmentScheduleInstance -Scope \$scope -Name "4cd7e26b-8eca-425c-969d-ec708c88bf18"

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.resources/get-azroleassignmentscheduleinstance>

