



Windows PowerShell Get-Help on Cmdlet 'Get-AzSecurityConnectorGitHubRepo'

PS: \>Get-HELP Get-AzSecurityConnectorGitHubRepo -Full

NAME

Get-AzSecurityConnectorGitHubRepo

SYNOPSIS

Returns a monitored GitHub repository.

SYNTAX

```
Get-AzSecurityConnectorGitHubRepo -OwnerName <String> -ResourceGroupName <String> -SecurityConnectorName
<String> [-SubscriptionId <String[]>] [-DefaultProfile
    <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy
    <Uri>] [-ProxyCredential <PSCredential>]
    [-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzSecurityConnectorGitHubRepo -OwnerName <String> -RepoName <String> -ResourceGroupName <String>
-SecurityConnectorName <String> [-SubscriptionId <String[]>]
    [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
    <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
    <PSCredential>] [-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```

Get-AzSecurityConnectorGitHubRepo -InputObject <ISecurityIdentity> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
    <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]

```

DESCRIPTION

Returns a monitored GitHub repository.

PARAMETERS

-OwnerName <String>

The GitHub owner name.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-RepoName <String>

The repository name.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SecurityConnectorName <String>

The security connector name.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String[]>

Azure subscription ID

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <ISecurityIdentity>

Identity Parameter

Required? true
Position? named
Default value
Accept pipeline input? true (ByValue)
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,
OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Security.Models.ISecurityIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Security.Models.IGitHubRepository

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <ISecurityIdentity>: Identity Parameter

[Apild <String>]: API revision identifier. Must be unique in the API Management service instance. Non-current revision has ;rev=n as a suffix where n is the revision number.

[GroupFqName <String>]: The GitLab group fully-qualified name.

[Id <String>]: Resource identity path

[OperationResultId <String>]: The operation result Id.

[OrgName <String>]: The Azure DevOps organization name.

[OwnerName <String>]: The GitHub owner name.

[ProjectName <String>]: The project name.

[RepoName <String>]: The repository name.

[ResourceGroupName <String>]: The name of the resource group within the user's subscription. The name is case sensitive.

insensitive.

[SecurityConnectorName <String>]: The security connector name.

[ServiceName <String>]: The name of the API Management service.

[SubscriptionId <String>]: Azure subscription ID

----- EXAMPLE 1 -----

```
PS C:\>Get-AzSecurityConnectorGitHubRepo -ResourceGroupName dfctest-sdk -SecurityConnectorName  
dfdsdktests-gh-01 -OwnerName dfdsdktests -RepoName TestApp0
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzSecurityConnectorGitHubRepo -ResourceGroupName dfctest-sdk -SecurityConnectorName  
dfdsdktests-gh-01 -OwnerName dfdsdktests
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.security/get-azsecurityconnectorgithubrepo>