



## ***Windows PowerShell Get-Help on Cmdlet 'Get-AzServiceBusKey'***

***PS:\>Get-HELP Get-AzServiceBusKey -Full***

### NAME

Get-AzServiceBusKey

### SYNOPSIS

Gets the SASKey of a ServiceBus namespace, queue or topic.

### SYNTAX

Get-AzServiceBusKey -Name <String> -NamespaceName <String> -ResourceGroupName <String> [-SubscriptionId <String[]>] [-DefaultProfile <PSObject>] [-AsJob] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [<CommonParameters>]

Get-AzServiceBusKey -Name <String> -NamespaceName <String> -ResourceGroupName <String> [-SubscriptionId <String[]>] -AliasName <String> [-DefaultProfile <PSObject>]

[-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [<CommonParameters>]

```

Get-AzServiceBusKey -Name <String> -NamespaceName <String> -ResourceGroupName <String> [-SubscriptionId
<String[]>] -TopicName <String> [-DefaultProfile <PSObject>]

[-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait]
[-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [<CommonParameters>]

```

```

Get-AzServiceBusKey -Name <String> -NamespaceName <String> -ResourceGroupName <String> [-SubscriptionId
<String[]>] -QueueName <String> [-DefaultProfile <PSObject>]

[-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait]
[-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [<CommonParameters>]

```

## DESCRIPTION

Gets the SASKey of a ServiceBus namespace, queue or topic.

## PARAMETERS

-Name <String>

The name of the Authorization Rule

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NamespaceName <String>

The name of ServiceBus namespace

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -SubscriptionId <String[]>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -AliasName <String>

The name of the Service Disaster Recovery Config.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -TopicName <String>

The name of the ServiceBus topic.

Required? true  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

**-QueueName <String>**

The name of the ServiceBus queue.

Required? true  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

**-DefaultProfile <PSObject>**

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

**-AsJob [<SwitchParameter>]**

Run the command as a job

Required? false  
Position? named  
Default value False  
Accept pipeline input? false  
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value            False  
Accept pipeline input?    false  
Accept wildcard characters? false

#### **-Proxy <Uri>**

The URI for the proxy server to use

Required?                false  
Position?                named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

#### **-ProxyCredential <PSCredential>**

Credentials for a proxy server to use for the remote call

Required?                false  
Position?                named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

#### **-ProxyUseDefaultCredentials [<SwitchParameter>]**

Use the default credentials for the proxy

Required?                false  
Position?                named  
Default value            False  
Accept pipeline input?    false  
Accept wildcard characters? false

#### **<CommonParameters>**

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,  
OutBuffer, PipelineVariable, and OutVariable. For more information, see  
about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

## INPUTS

## OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.ServiceBus.Models.IAccessKeys

### ----- EXAMPLE 1 -----

```
PS C:\>Get-AzServiceBusKey -ResourceGroupName myResourceGroup -NamespaceName myNamespace -Name  
RootManageSharedAccessKey
```

### ----- EXAMPLE 2 -----

```
PS C:\>Get-AzServiceBusKey -ResourceGroupName myResourceGroup -NamespaceName myNamespace  
-QueueName queue1 -Name RootManageSharedAccessKey
```

### ----- EXAMPLE 3 -----

```
PS C:\>Get-AzServiceBusKey -ResourceGroupName myResourceGroup -NamespaceName myNamespace -TopicName
```

topic1 -Name RootManageSharedAccessKey

#### RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.servicebus/get-azservicebuskey>