



Windows PowerShell Get-Help on Cmdlet 'Get-AzServiceBusSubscription'

PS:\>Get-HELP Get-AzServiceBusSubscription -Full

NAME

Get-AzServiceBusSubscription

SYNOPSIS

Returns a subscription description for the specified topic.

SYNTAX

```
Get-AzServiceBusSubscription -NamespaceName <String> -ResourceGroupName <String> [-SubscriptionId <String[]>]
-TopicName <String> [-Skip <Int32>] [-Top <Int32>]
[-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzServiceBusSubscription -Name <String> -TopicInputObject <IServiceBusIdentity> [-DefaultProfile <PSObject>]
[-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzServiceBusSubscription -Name <String> -TopicName <String> -NamespaceInputObject <IServiceBusIdentity>
```

```
[-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend  
    <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]  
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzServiceBusSubscription -Name <String> -NamespaceName <String> -ResourceGroupName <String>  
[-SubscriptionId <String[]>] -TopicName <String> [-DefaultProfile  
    <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy  
<Uri>] [-ProxyCredential <PSCredential>]  
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzServiceBusSubscription -InputObject <IServiceBusIdentity> [-DefaultProfile <PSObject>] [-Break]  
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend  
    <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]  
[<CommonParameters>]
```

DESCRIPTION

Returns a subscription description for the specified topic.

PARAMETERS

-Name <String>

The subscription name.

Required?	true
-----------	------

Position?	named
-----------	-------

Default value

Accept pipeline input?	false
------------------------	-------

Accept wildcard characters?	false
-----------------------------	-------

-NamespaceName <String>

The namespace name

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ResourceGroupName <String>

Name of the Resource group within the Azure subscription.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String[]>

Subscription credentials that uniquely identify a Microsoft Azure subscription.

The subscription ID forms part of the URI for every service call.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-TopicName <String>

The topic name.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <IServiceBusIdentity>

Identity Parameter

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-NamespaceInputObject <IServiceBusIdentity>

Identity Parameter

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-TopicInputObject <IServiceBusIdentity>

Identity Parameter

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Skip <Int32>

Skip is only used if a previous operation returned a partial result.

If a previous response contains a nextLink element, the value of the nextLink element will include a skip parameter that specifies a starting point to use for subsequent calls.

Required? false
Position? named
Default value 0
Accept pipeline input? false
Accept wildcard characters? false

-Top <Int32>

May be used to limit the number of results to the most recent N usageDetails.

Required? false
Position? named
Default value 0
Accept pipeline input? false
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.ServiceBus.Models.IServiceBusIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.ServiceBus.Models.ISbSubscription

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about_Hash_Tables.

INPUTOBJECT <IServiceBusIdentity>: Identity Parameter

[Alias <String>]: The Disaster Recovery configuration name

[AuthorizationRuleName <String>]: The authorization rule name.

[ConfigName <String>]: The configuration name. Should always be "\$default".

[Id <String>]: Resource identity path

[NamespaceName <String>]: The namespace name

[PrivateEndpointConnectionName <String>]: The PrivateEndpointConnection name

[QueueName <String>]: The queue name.

[ResourceGroupName <String>]: Name of the Resource group within the Azure subscription.

[RuleName <String>]: The rule name.

[SubscriptionId <String>]: Subscription credentials that uniquely identify a Microsoft Azure subscription. The subscription ID forms part of the URI for every service call.

[SubscriptionName <String>]: The subscription name.

[TopicName <String>]: The topic name.

NAMESPACEINPUTOBJECT <IServiceBusIdentity>: Identity Parameter

[Alias <String>]: The Disaster Recovery configuration name

[AuthorizationRuleName <String>]: The authorization rule name.

[ConfigName <String>]: The configuration name. Should always be "\$default".

[Id <String>]: Resource identity path

[NamespaceName <String>]: The namespace name

[PrivateEndpointConnectionName <String>]: The PrivateEndpointConnection name

[QueueName <String>]: The queue name.

[ResourceGroupName <String>]: Name of the Resource group within the Azure subscription.

[RuleName <String>]: The rule name.

[SubscriptionId <String>]: Subscription credentials that uniquely identify a Microsoft Azure subscription. The subscription ID forms part of the URI for every service call.

[SubscriptionName <String>]: The subscription name.

[TopicName <String>]: The topic name.

TOPICINPUTOBJECT <IServiceBusIdentity>: Identity Parameter

[Alias <String>]: The Disaster Recovery configuration name

[AuthorizationRuleName <String>]: The authorization rule name.

[ConfigName <String>]: The configuration name. Should always be "\$default".

[Id <String>]: Resource identity path

[NamespaceName <String>]: The namespace name

[PrivateEndpointConnectionName <String>]: The PrivateEndpointConnection name

[QueueName <String>]: The queue name.

[ResourceGroupName <String>]: Name of the Resource group within the Azure subscription.

[RuleName <String>]: The rule name.

[SubscriptionId <String>]: Subscription credentials that uniquely identify a Microsoft Azure subscription. The subscription ID forms part of the URI for every service call.

[SubscriptionName <String>]: The subscription name.

[TopicName <String>]: The topic name.

----- EXAMPLE 1 -----

```
PS C:\>Get-AzServiceBusSubscription -ResourceGroupName myResourceGroup -NamespaceName myNamespace  
-TopicName myTopic -Name 'sub$$$D'
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzServiceBusSubscription -ResourceGroupName myResourceGroup -NamespaceName myNamespace  
-TopicName myTopic
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.servicebus/get-azservicebussubscription>

<https://msdn.microsoft.com/en-us/library/azure/mt639402.aspx>

<https://msdn.microsoft.com/en-us/library/azure/mt639400.aspx>