



Windows PowerShell Get-Help on Cmdlet 'Get-AzStaticWebAppBuild'

PS: \>Get-HELP Get-AzStaticWebAppBuild -Full

NAME

Get-AzStaticWebAppBuild

SYNOPSIS

Description for Gets the details of a static site build.

SYNTAX

Get-AzStaticWebAppBuild -Name <String> -ResourceGroupName <String> [-SubscriptionId <String[]>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend

<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [<CommonParameters>]

Get-AzStaticWebAppBuild -EnvironmentName <String> -Name <String> -ResourceGroupName <String> [-SubscriptionId <String[]>] [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]

[<CommonParameters>]

Get-AzStaticWebAppBuild -InputObject <IWebsitesIdentity> [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend

<SendAsyncStep[]> [-HttpPipelinePrepend
 <SendAsyncStep[]> [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]

DESCRIPTION

Description for Gets the details of a static site build.

PARAMETERS

-EnvironmentName <String>

The stage site identifier.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <String>

Name of the static site.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

Name of the resource group to which the resource belongs.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String[]>

Your Azure subscription ID.

This is a GUID-formatted string (e.g.

00000000-0000-0000-0000-000000000000).

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IWebsitesIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Websites.Models.IWebsitesIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Websites.Models.Api20201201.IStaticSiteBuildArmResource

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IWebsitesIdentity>: Identity Parameter

[AuthProvider <String>]: The auth provider for the users.

[DomainName <String>]: The custom domain name.

[EnvironmentName <String>]: The stage site identifier.

[FunctionAppName <String>]: Name of the function app registered with the static site build.

[Id <String>]: Resource identity path

[JobHistoryId <String>]: History ID.

[Location <String>]: Location where you plan to create the static site.

[Name <String>]: Name of the static site.

[PrivateEndpointConnectionName <String>]: Name of the private endpoint connection.

[ResourceGroupName <String>]: Name of the resource group to which the resource belongs.

[Slot <String>]: Name of the deployment slot. If a slot is not specified, the API deletes a deployment for the production slot.

[SubscriptionId <String>]: Your Azure subscription ID. This is a GUID-formatted string (e.g. 00000000-0000-0000-0000-000000000000).

[UserId <String>]: The user id of the user.

[WebJobName <String>]: Name of Web Job.

----- EXAMPLE 1 -----

```
PS C:\>Get-AzStaticWebAppBuild -ResourceGroupName azure-rg-test -Name staticweb-portal04
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzStaticWebAppBuild -ResourceGroupName azure-rg-test -Name staticweb-portal04 -EnvironmentName  
'default'
```

----- EXAMPLE 3 -----

```
PS C:\>Get-AzStaticWebAppBuild -ResourceGroupName azure-rg-test -Name staticweb-portal04 |  
Get-AzStaticWebAppBuild
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.websites/get-azstaticwebappbuild>