



### ***Windows PowerShell Get-Help on Cmdlet 'Get-AzStorageMoverProject'***

***PS:\>Get-HELP Get-AzStorageMoverProject -Full***

#### **NAME**

Get-AzStorageMoverProject

#### **SYNOPSIS**

Gets a Project resource.

#### **SYNTAX**

```
Get-AzStorageMoverProject -ResourceGroupName <String> -StorageMoverName <String> [-SubscriptionId <String[]>]
[-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]

[<CommonParameters>]
```

```
Get-AzStorageMoverProject -Name <String> -ResourceGroupName <String> -StorageMoverName <String>
[-SubscriptionId <String[]>] [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]

[<CommonParameters>]
```

```
Get-AzStorageMoverProject -InputObject <IStorageMoverIdentity> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
    <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

## DESCRIPTION

Gets a Project resource.

## PARAMETERS

**-Name <String>**

The name of the Project resource.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

**-ResourceGroupName <String>**

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

**-StorageMoverName <String>**

The name of the Storage Mover resource.

Required? true  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

-SubscriptionId <String[]>

The ID of the target subscription.

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

-InputObject <IStorageMoverIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true  
Position? named  
Default value  
Accept pipeline input? true (ByValue)  
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false  
Position? named  
Default value  
Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position?                named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

**-ProxyCredential <PSCredential>**

Credentials for a proxy server to use for the remote call

Required?                false  
Position?                named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

**-ProxyUseDefaultCredentials [<SwitchParameter>]**

Use the default credentials for the proxy

Required?                false  
Position?                named  
Default value             False  
Accept pipeline input?    false  
Accept wildcard characters? false

**<CommonParameters>**

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about\\_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

**INPUTS**

Microsoft.Azure.PowerShell.Cmdlets.StorageMover.Models.IStorageMoverIdentity

## OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.StorageMover.Models.Api20231001.IProject

## NOTES

### COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about\_Hash\_Tables.

INPUTOBJECT <IStorageMoverIdentity>: Identity Parameter

[AgentName <String>]: The name of the Agent resource.

[EndpointName <String>]: The name of the Endpoint resource.

[Id <String>]: Resource identity path

[JobDefinitionName <String>]: The name of the Job Definition resource.

[JobRunName <String>]: The name of the Job Run resource.

[ProjectName <String>]: The name of the Project resource.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[StorageMoverName <String>]: The name of the Storage Mover resource.

[SubscriptionId <String>]: The ID of the target subscription.

### ----- EXAMPLE 1 -----

```
PS C:\>$projectList = Get-AzStorageMoverProject -ResourceGroupName myResourceGroup -StorageMoverName myStorageMover
```

----- EXAMPLE 2 -----

```
PS C:\>$projectList = Get-AzStorageMoverProject -ResourceGroupName myResourceGroup -StorageMoverName  
myStorageMover -Name myProject1
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.storage/mover/get-azstorageproject>