



Windows PowerShell Get-Help on Cmdlet 'Get-AzSupportCommunication'

PS:\>Get-HELP Get-AzSupportCommunication -Full

NAME

Get-AzSupportCommunication

SYNOPSIS

Returns communication details for a support ticket.

SYNTAX

```
Get-AzSupportCommunication [-SubscriptionId <String[]>] -SupportTicketName <String> [-Filter <String>] [-Top <Int32>]
[-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]
```

```
Get-AzSupportCommunication -Name <String> -SupportTicketInputObject <ISupportIdentity> [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzSupportCommunication -Name <String> [-SubscriptionId <String[]>] -SupportTicketName <String> [-DefaultProfile
```

```

<PSObject>] [-Break] [-HttpPipelineAppend
    <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]

    Get-AzSupportCommunication -InputObject <ISupportIdentity> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
    <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]

```

DESCRIPTION

Returns communication details for a support ticket.

PARAMETERS

-Name <String>

Communication name.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String[]>

The ID of the target subscription.

The value must be an UUID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SupportTicketName <String>

Support ticket name.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <ISupportIdentity>

Identity Parameter

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-SupportTicketInputObject <ISupportIdentity>

Identity Parameter

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Filter <String>

The filter to apply on the operation.

You can filter by communicationType and createdDate properties.

CommunicationType supports Equals ('eq') operator and createdDate supports Greater Than ('gt') and Greater Than or

Equals ('ge') operators.

You may combine the CommunicationType and CreatedDate filters by Logical And ('and') operator.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Top <Int32>

The number of values to return in the collection.
Default is 10 and max is 10.

Required? false
Position? named
Default value 0
Accept pipeline input? false
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.
Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Support.Models.ISupportIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Support.Models.ICommunicationDetails

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <ISupportIdentity>: Identity Parameter

[ChatTranscriptName <String>]: ChatTranscript name.

[CommunicationName <String>]: Communication name.

[FileName <String>]: File Name

[FileWorkspaceName <String>]: File Workspace Name

[Id <String>]: Resource identity path

[ProblemClassificationName <String>]: Name of problem classification.

[ServiceName <String>]: Name of the Azure service.

[SubscriptionId <String>]: The ID of the target subscription. The value must be an UUID.

[SupportTicketName <String>]: Support ticket name.

SUPPORTTICKETINPUTOBJECT <ISupportIdentity>: Identity Parameter

[ChatTranscriptName <String>]: ChatTranscript name.

[CommunicationName <String>]: Communication name.

[FileName <String>]: File Name

[FileWorkspaceName <String>]: File Workspace Name

[Id <String>]: Resource identity path

[ProblemClassificationName <String>]: Name of problem classification.

[ServiceName <String>]: Name of the Azure service.

[SubscriptionId <String>]: The ID of the target subscription. The value must be an UUID.

[SupportTicketName <String>]: Support ticket name.

----- EXAMPLE 1 -----

PS

C:\>Get-AzSupportCommunication

-SupportTicketName

"3366336e-bc3faf4f-3970e063-e033-441f-8a49-1e6e1b55f05d"

----- EXAMPLE 2 -----

```
PS C:\>Get-AzSupportCommunication -SupportTicketName  
"3366336e-bc3faf4f-3970e063-e033-441f-8a49-1e6e1b55f05d" -Name "590629b9-44cb-ee11-9079-6045bdef700d"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.support/get-azsupportcommunication>