



Windows PowerShell Get-Help on Cmdlet 'Get-AzSupportFile'

PS:\>Get-HELP Get-AzSupportFile -Full

NAME

Get-AzSupportFile

SYNOPSIS

Returns details of a specific file in a work space.

SYNTAX

```
Get-AzSupportFile [-SubscriptionId <String[]>] -WorkspaceName <String> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzSupportFile -Name <String> -FileWorkspaceInputObject <ISupportIdentity> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```
Get-AzSupportFile -Name <String> [-SubscriptionId <String[]>] -WorkspaceName <String> [-DefaultProfile <PSObject>]
[-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
```

[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]

Get-AzSupportFile -InputObject <ISupportIdentity> [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[<CommonParameters>]

DESCRIPTION

Returns details of a specific file in a work space.

PARAMETERS

-Name <String>

File Name

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String[]>

The ID of the target subscription.

The value must be an UUID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-WorkspaceName <String>

File Workspace Name

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <ISupportIdentity>

Identity Parameter

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-FileWorkspaceInputObject <ISupportIdentity>

Identity Parameter

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Support.Models.IFileDetails

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

FILEWORKSPACEINPUTOBJECT <ISupportIdentity>: Identity Parameter

[ChatTranscriptName <String>]: ChatTranscript name.

[CommunicationName <String>]: Communication name.

[FileName <String>]: File Name

[FileWorkspaceName <String>]: File Workspace Name

[Id <String>]: Resource identity path

[ProblemClassificationName <String>]: Name of problem classification.

[ServiceName <String>]: Name of the Azure service.

[SubscriptionId <String>]: The ID of the target subscription. The value must be an UUID.

[SupportTicketName <String>]: Support ticket name.

INPUTOBJECT <ISupportIdentity>: Identity Parameter

[ChatTranscriptName <String>]: ChatTranscript name.

[CommunicationName <String>]: Communication name.

[FileName <String>]: File Name

[FileWorkspaceName <String>]: File Workspace Name

[Id <String>]: Resource identity path

[ProblemClassificationName <String>]: Name of problem classification.

[ServiceName <String>]: Name of the Azure service.

[SubscriptionId <String>]: The ID of the target subscription. The value must be an UUID.

[SupportTicketName <String>]: Support ticket name.

----- EXAMPLE 1 -----

```
PS C:\>Get-AzSupportFile -WorkspaceName "testworkspace"
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzSupportFile -Name "test.txt" -WorkspaceName "testworkspace"
```

----- EXAMPLE 3 -----

```
PS C:\>Get-AzSupportFile -WorkspaceName "2402084010005835"
```

----- EXAMPLE 4 -----

```
PS C:\>Get-AzSupportFile -Name "test.txt" -WorkspaceName "2402084010005835"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.support/get-azsupportfile>