



Windows PowerShell Get-Help on Cmdlet 'Get-AzSynapseKustoPoolAttachedDatabaseConfiguration'

PS:\>Get-HELP Get-AzSynapseKustoPoolAttachedDatabaseConfiguration -Full

NAME

Get-AzSynapseKustoPoolAttachedDatabaseConfiguration

SYNOPSIS

Returns an attached database configuration.

SYNTAX

```
Get-AzSynapseKustoPoolAttachedDatabaseConfiguration -KustoPoolName <String> -ResourceGroupName <String>
[-SubscriptionId <String[]>] -WorkspaceName <String>
[-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials] [<CommonParameters>]

Get-AzSynapseKustoPoolAttachedDatabaseConfiguration -AttachedDatabaseConfigurationName <String>
-KustoPoolName <String> -ResourceGroupName <String> [-SubscriptionId
<String[]>] -WorkspaceName <String> [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy
<Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [<CommonParameters>]
```

```

Get-AzSynapseKustoPoolAttachedDatabaseConfiguration -InputObject <ISynapseIdentity> [-DefaultProfile <PSObject>]
[-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
                [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [<CommonParameters>]

```

DESCRIPTION

Returns an attached database configuration.

PARAMETERS

-AttachedDatabaseConfigurationName <String>

The name of the attached database configuration.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-KustoPoolName <String>

The name of the Kusto pool.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String[]>

The ID of the target subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-WorkspaceName <String>

The name of the workspace

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <ISynapseIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true
Position? named
Default value
Accept pipeline input? true (ByValue)
Accept wildcard characters? false

`-DefaultProfile <PSObject>`

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

`-Break [<SwitchParameter>]`

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

`-HttpPipelineAppend <SendAsyncStep[]>`

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

`-HttpPipelinePrepend <SendAsyncStep[]>`

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see `about_CommonParameters` (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Synapse.Models.ISynapseIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Synapse.Models.Api20210601Preview.IAttachedDatabaseConfiguration

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run `Get-Help about_Hash_Tables`.

INPUTOBJECT <ISynapseIdentity>: Identity Parameter

[AttachedDatabaseConfigurationName <String>]: The name of the attached database configuration.

[DataConnectionName <String>]: The name of the data connection.

[DatabaseName <String>]: The name of the database in the Kusto pool.

[Id <String>]: Resource identity path

[KustoPoolName <String>]: The name of the Kusto pool.

[Location <String>]: The name of Azure region.

[PrincipalAssignmentName <String>]: The name of the Kusto principalAssignment.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SubscriptionId <String>]: The ID of the target subscription.

[WorkspaceName <String>]: The name of the workspace

----- EXAMPLE 1 -----

```
PS C:\>Get-AzSynapseKustoPoolAttachedDatabaseConfiguration -ResourceGroupName testrg -WorkspaceName testws  
-KustoPoolName testfollowerkustopool
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzSynapseKustoPoolAttachedDatabaseConfiguration -ResourceGroupName testrg -WorkspaceName testws  
-KustoPoolName testfollowerkustopool -Name  
followerconfiguration
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.synapse/get-azsynapsekustopoolattacheddatabaseconfiguration>