



Windows PowerShell Get-Help on Cmdlet 'Get-AzTenantDeploymentOperation'

PS:\>Get-HELP Get-AzTenantDeploymentOperation -Full

NAME

Get-AzTenantDeploymentOperation

SYNOPSIS

Get deployment operation for deployment at tenant scope

SYNTAX

```

Get-AzTenantDeploymentOperation                                [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -DeploymentName
<System.String> [-OperationId <System.String>] [-Pre] [<CommonParameters>]

```

```

Get-AzTenantDeploymentOperation                                [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -DeploymentObject
<Microsoft.Azure.Commands.ResourceManager.Cmdlets.SdkModels.PSDeployment> [-Pre] [<CommonParameters>]

```

DESCRIPTION

The Get-AzTenantDeploymentOperation cmdlet lists all the operations that were part of deployment at the current tenant scope to help you identify and give more

information about the exact operations that failed for a particular deployment.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-DeploymentName <System.String>

The deployment name.

Required? true

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-DeploymentObject <Microsoft.Azure.Commands.ResourceManager.Cmdlets.SdkModels.PSDeployment>

The deployment object.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-OperationId <System.String>

The deployment operation Id.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-Pre <System.Management.Automation.SwitchParameter>

When set, indicates that the cmdlet should use pre-release API versions when automatically determining which version to use.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.ResourceManager.Cmdlets.SdkModels.PSDeployment

OUTPUTS

Microsoft.Azure.Commands.ResourceManager.Cmdlets.SdkModels.PSDeploymentOperation

NOTES

- Example 1: Get deployment operations given a deployment name -

```
Get-AzTenantDeploymentOperation -DeploymentName Deploy01
```

Gets deployment operations with name "Deploy01" at the current tenant scope.

Example 2: Get a deployment and get its deployment operations

```
Get-AzTenantDeployment -Name Deploy01 | Get-AzTenantDeploymentOperation
```

This command gets the deployment "Deploy01" at the current tenant scope and get its deployment operations.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.resources/get-aztenantdeploymentoperation>