



Windows PowerShell Get-Help on Cmdlet 'Get-AzTenantDeploymentWhatIfResult'

PS:\>Get-HELP Get-AzTenantDeploymentWhatIfResult -Full

NAME

Get-AzTenantDeploymentWhatIfResult

SYNOPSIS

Gets a template What-If result for a deployment at tenant scope.

SYNTAX

```

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] -Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly |
FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateFile <System.String> [<CommonParameters>]

```

```

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] -Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly |
FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateFile <System.String> -TemplateParameterObject <System.Collections.Hashtable> [<CommonParameters>]

```

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] -Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly |
FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateFile <System.String> -TemplateParameterFile <System.String> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] -Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly |
FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateFile <System.String> -TemplateParameterUri <System.String> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] -Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly |
FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateObject <System.Collections.Hashtable> -TemplateParameterObject <System.Collections.Hashtable>
[<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] -Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly |
FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateObject <System.Collections.Hashtable> -TemplateParameterFile <System.String> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] -Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly |
FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateObject <System.Collections.Hashtable> -TemplateParameterUri <System.String> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType

<System.String[]> [-Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly | FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateObject <System.Collections.Hashtable> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] [-Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly | FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateParameterFile <System.String> -TemplateUri <System.String> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] [-Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly | FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateParameterFile <System.String> -TemplateSpecId <System.String> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] [-Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly | FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateParameterFile <System.String> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] [-Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly | FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateParameterObject <System.Collections.Hashtable> -TemplateUri <System.String> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] [-Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly | FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateParameterObject <System.Collections.Hashtable> -TemplateSpecId <System.String> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] -Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly |
FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateParameterUri <System.String> -TemplateUri <System.String> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] -Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly |
FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateParameterUri <System.String> -TemplateSpecId <System.String> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] -Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly |
FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateSpecId <System.String> [<CommonParameters>]

Get-AzTenantDeploymentWhatIfResult [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-ExcludeChangeType
<System.String[]>] -Location <System.String> [-Name <System.String>] [-Pre] [-ResultFormat {ResourceIdOnly |
FullResourcePayloads}] [-SkipTemplateParameterPrompt]
-TemplateUri <System.String> [<CommonParameters>]

DESCRIPTION

The Get-AzTenantDeploymentWhatIfResult cmdlet gets the ARM template What-If result for a template deployment at the specified tenant scope. It returns a list of

changes indicating what resources will be updated if the deployment is applied without making any changes to real resources. To specify the format for the returning result, use the ResultFormat parameter.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-ExcludeChangeType <System.String[]>

Comma-separated list of resource change types to be excluded from What-If results.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Location <System.String>

The location to store deployment data.

Required? true

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Name <System.String>

The name of the deployment it's going to create. If not specified, defaults to the template file name when a template file is provided; defaults to the current

time when a template object is provided, e.g. "20131223140835".

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-Pre <System.Management.Automation.SwitchParameter>

When set, indicates that the cmdlet should use pre-release API versions when automatically determining which version to use.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-ResultFormat <Microsoft.Azure.Management.Resources.Models.WhatIfResultFormat>

The What-If result format.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-SkipTemplateParameterPrompt <System.Management.Automation.SwitchParameter>

Skips the PowerShell dynamic parameter processing that checks if the provided template parameter contains all necessary parameters used by the template. This

check would prompt the user to provide a value for the missing parameters, but providing the

-SkipTemplateParameterPrompt will ignore this prompt and error out

immediately if a parameter was found not to be bound in the template. For non-interactive scripts,

-SkipTemplateParameterPrompt can be provided to provide a

better error message in the case where not all required parameters are satisfied.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-TemplateFile <System.String>

Local path to the template file. Supported template file type: json and bicep.

Required?	true
Position?	named
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-TemplateObject <System.Collections.Hashtable>

A hash table which represents the template.

Required?	true
Position?	named
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-TemplateParameterFile <System.String>

Parameter file to use for the template.

Required?	true
Position?	named
Default value	None
Accept pipeline input?	True (ByPropertyName)

Accept wildcard characters? false

-TemplateParameterObject <System.Collections.Hashtable>

A hash table which represents the parameters.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-TemplateParameterUri <System.String>

Uri to the template parameter file.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-TemplateSpecId <System.String>

Resource ID of the templateSpec to be deployed.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-TemplateUri <System.String>

Uri to the template file.

Required? true

Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

System.String

System.Collections.Hashtable

OUTPUTS

Microsoft.Azure.Commands.ResourceManager.Cmdlets.SdkModels.Deployments.PSWhatIfOperationResult

NOTES

----- Example 1: Get a What-If result at tenant scope -----

Get-AzTenantDeploymentWhatIfResult `

-DeploymentName "deploy-01" `

```
-Location "West US" `
-TemplateFile "D:\Azure\Templates\ServiceTemplate.json" `
-TemplateParameterFile "D:\Azure\Templates\ServiceParameters.json" `
-ResultFormat "FullResourcePayloads"
```

This command gets a What-If result at tenant scope by using a custom template file and a parameter file on disk. The command uses the Location parameter to specify

where to store the deployment data. The command uses the TemplateFile parameter to specify a template file. The command uses the TemplateParameterFile parameter to

specify a template parameter file. The command uses the ResultFormat parameter to set the What-If result to include full resource payloads.

Example 2: Get a What-If result at tenant scope with ResourceIdOnly

```
Get-AzTenantDeploymentWhatIfResult `
-DeploymentName "deploy-01" `
-Location "West US" `
-TemplateFile "D:\Azure\Templates\ServiceTemplate.json" `
-TemplateParameterFile "D:\Azure\Templates\ServiceParameters.json" `
-ResultFormat "ResourceIdOnly"
```

This command gets a What-If result at tenant scope by using a custom template file and a parameter file on disk. The command uses the Location parameter to specify

where to store the deployment data. The command uses the TemplateFile parameter to specify a template file. The command uses the TemplateParameterFile parameter to

specify a template parameter file. The command uses the ResultFormat parameter to set the What-If result to only contain resource IDs.

---- Example 3: Use a .bicepparam file to calculate What-If ----

```
Get-AzTenantDeploymentWhatIfResult -Location "West US" -TemplateParameterFile ".\parameters.bicepparam"
```

This command gets a What-If result at the current tenant scope by using a .bicepparam file on disk. The command uses the TemplateParameterFile parameter to specify a .bicepparam file.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.resources/get-aztenantdeploymentwhatifresult>