



Windows PowerShell Get-Help on Cmdlet 'Get-AzUserAssignedIdentityAssociatedResource'

PS:\>Get-HELP Get-AzUserAssignedIdentityAssociatedResource -Full

NAME

Get-AzUserAssignedIdentityAssociatedResource

SYNOPSIS

Lists the associated resources for this identity.

SYNTAX

```
Get-AzUserAssignedIdentityAssociatedResource -Name <String> -ResourceGroupName <String> [-SubscriptionId
<String>] [-Filter <String>] [-Orderby <String>] [-Skip
<Int32>] [-Skiptoken <String>] [-Top <Int32>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>]
[-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]
```

DESCRIPTION

Lists the associated resources for this identity.

PARAMETERS

-Name <String>

The name of the identity resource.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the Resource Group to which the identity belongs.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String[]>

The Id of the Subscription to which the identity belongs.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Filter <String>

OData filter expression to apply to the query.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Orderby <String>

OData orderBy expression to apply to the query.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Skip <Int32>

Number of records to skip.

Required? false

Position? named

Default value 0

Accept pipeline input? false

Accept wildcard characters? false

-Skiptoken <String>

A skip token is used to continue retrieving items after an operation returns a partial result.

If a previous response contains a nextLink element, the value of the nextLink element will include a skipToken parameter that specifies a starting point to use

for subsequent calls.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Top <Int32>

Number of records to return.

Required? false

Position? named

Default value 0

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-WhatIf [<SwitchParameter>]

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-Confirm [<SwitchParameter>]

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

OUTPUTS

----- EXAMPLE 1 -----

```
PS C:\>Get-AzUserAssignedIdentityAssociatedResource -ResourceGroupName azure-rg-test -Name uai-pwsh01
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzUserAssignedIdentityAssociatedResource -ResourceGroupName azure-rg-test -Name uai-pwsh01 `
-Filter "type eq 'microsoft.compute/virtualmachines' and contains(name, 'default')"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.managedserviceidentity/get-azuserassignedidentityassociatedresource>