



Windows PowerShell Get-Help on Cmdlet 'Import-AzRecoveryServicesAsrVaultSettingsFile'

PS:\>Get-HELP Import-AzRecoveryServicesAsrVaultSettingsFile -Full

NAME

Import-AzRecoveryServicesAsrVaultSettingsFile

SYNOPSIS

Imports the specified ASR vault settings file to set the vault context(PowerShell session context) for subsequent ASR operations in the PowerShell session.

SYNTAX

```
Import-AzRecoveryServicesAsrVaultSettingsFile [-Path] <System.String> [-DefaultProfile  
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Confirm] [-WhatIf]  
[<CommonParameters>]
```

DESCRIPTION

The Import-AzRecoveryServicesAsrVaultSettingsFile cmdlet imports the Azure Site Recovery vault settings file. The vault settings file is used to set the vault context for subsequent Azure Site Recovery operations in the current session.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Path <System.String>

Specifies the folder path of the ASR vault settings file. This file can be downloaded from the Recovery Services vault portal and stored locally.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

System.String

OUTPUTS

Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRVaultSettings

NOTES

----- Example 1 -----

```
$VaultSettings = Import-AzRecoveryServicesAsrVaultSettingsFile -Path $FilePath
```

Imports the specified Recovery Services vault settings file and returns settings of the imported vault.

RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.recoveryservices/import-azrecoveryservicesasrvaultsettingsfile>

Azure Recovery Services cmdlets